



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Identification of the preparation HP ElectroInk® Invisible Ink B
MPS-2471-42

Use of the preparation For use with HP Indigo Press series 1000 & 2000

Manufacturer information Hewlett Packard Company
Limburglaan 5
6221 SH Maastricht, The Netherlands

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209
(Direct) 1-503-494-7199

General information telephone number

HP Customer Care Line 1-800-474-6836
(Toll-free) 1-800-474-6836
(Direct) 1-208-323-2551

Date prepared Aug 22, 2006

MSDS number 167685

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component/substance	CAS number	% by weight
Petroleum hydrocarbon	90622-58-5	< 90
Composition comments	This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Communication Standard).	

3. HAZARDS IDENTIFICATION

Emergency overview Contact with skin and eyes may result in irritation.

Acute health effects Any potential hazards are presumed to be due to exposure to the components.

Skin contact

Petroleum hydrocarbon
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye contact

Petroleum hydrocarbon
Slightly irritating but does not injure eye tissue. Direct contact with the eye may cause discomfort and redness.

Inhalation

As a paste, the risk for lung damage is unlikely.

Petroleum hydrocarbon
Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Ingestion

Petroleum hydrocarbon
Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Potential health effects

Routes of exposure Potential routes of exposure to this product are skin and eye contact, ingestion and inhalation.

Chronic health effects Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization reaction.



MATERIAL SAFETY DATA SHEET

Carcinogenicity

None of the components present in this formulation at concentrations equal to or greater than 0.1% are listed by EU, MAK, IARC, NTP or OSHA.

4. FIRST AID MEASURES

First aid procedures

Skin

Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.

Eye

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention. Do not apply neutralizing agents.

Inhalation

If overcome by vapor, remove person from exposure to fresh air. If breathing is difficult, give oxygen. If symptoms persist, get medical attention.

Ingestion

Do not induce vomiting. Never give anything by mouth to an unconscious person. If ingestion of a large amount does occur, seek medical attention.

5. FIRE FIGHTING MEASURES

Flash point and method

> 64 °C (based on petroleum hydrocarbon); Pensky-Martens Closed Cup

Auto ignition temperature

> 200 °C (based on petroleum hydrocarbon)

Hazardous combustion products

Refer to section 10.

Extinguishing media

Suitable extinguishing media: Dry chemical, CO₂, water spray or regular foam.

Unsuitable extinguishing media

None known.

Fire fighting equipment/instructions

Move containers from fire area if you can do it without risk. Evacuate area and fight fire from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear appropriate personal protective equipment.

Environmental precautions

Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Procedures if material is released or spilled

Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or other sealed container.
Dispose of in compliance with federal, state, and local regulations.
See also section 13 Disposal considerations.

Evacuation procedures

In case of large spills, follow all facility emergency response procedures.

7. HANDLING AND STORAGE

Handling

Avoid prolonged or repeated skin contact with this material. Avoid contact with skin, eyes and clothing.
Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.

Storage

Keep away from excessive heat or cold. Store in a cool and shaded area. Do not store in direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Manufacturer recommended exposure limit based on petroleum hydrocarbon at > 75%. TWA = 171ppm (1200 mg/m³).

Personal protective equipment

General

Use personal protective equipment to minimize exposure to skin and eye.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.



MATERIAL SAFETY DATA SHEET

Exposure guidelines Use in a well ventilated area.

9. PHYSICAL & CHEMICAL PROPERTIES

Boiling point	188 °C (based on petroleum hydrocarbon)
Specific gravity	0.801 g/mL
VOC content	675 g/L
Flash point	> 64 °C (based on petroleum hydrocarbon)
Appearance	Paste
Odor	mild hydrocarbon-like
Oxidizing properties	Not applicable
Color	blue

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability	Stable under recommended storage conditions.
Hazardous polymerization	Will not occur.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatibility	This product may react with strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

The ink formulation has not been tested.
Refer to Section 3 for potential health effects and Section 4 for first aid measures.

12. ECOLOGICAL INFORMATION

Aquatic toxicity	This product has not been tested for ecological effects.
-------------------------	--

13. DISPOSAL CONSIDERATIONS

Disposal instructions	Dispose of in compliance with federal, state, and local regulations.
------------------------------	--

14. TRANSPORTATION INFORMATION

General	Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.
----------------	---

IATA

Proper shipping name	Not applicable
Hazard class	Not applicable
Packaging exceptions	none
Identification number (UN)	none
Packing group	none

15. REGULATORY INFORMATION

US federal regulations	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA. US TSCA 12(b): Does not contain listed chemicals.
-------------------------------	---



MATERIAL SAFETY DATA SHEET

HMIS ratings	Health:	1
	Flammability:	2
	Physical hazard:	0
NFPA ratings	Health:	1
	Flammability:	2
	Instability:	0

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories
Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

16. OTHER INFORMATION

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).

Issue date Aug 22 2006 11:28AM

Revision 3

Replaces sheet dated Aug 15 2006 8:05PM

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.



MATERIAL SAFETY DATA SHEET

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds