

Increase business opportunities with a printer that delivers unrivaled versatility for outdoor and indoor applications. (1 Experience the ease of reliable HP Designjet printing. Attract the attention of environmentally conscious customers.



UNRIVALED VERSATILITY FROM ONE PRINTING SYSTEM(1

- Produce outdoor signage with durability comparable to ecosolvent inks.(2
- Achieve high-quality results—that meet clients' branding requirements—for all your indoor signage applications, from exhibition graphics to interior decorations.
- Print on a wide range of media, including coated media or polyester fabric⁽³⁾ and low-cost papers without treatments.
- Produce vehicle wraps with HP Latex Inks that outperform ecosolvent inks. HP is the only company that offers and warrants the entire printing system for vehicle wraps⁽⁴⁾ with the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl and HP Clear Gloss Cast Overlaminate. (5
- Expect the most out of each application when you use the broad portfolio of Original HP printing materials.

EASY, AUTOMATIC, LOW MAINTENANCE PRINTING

- Experience easy, unattended printing with HP Thermal Inkjet printheads and automatic maintenance.
- Experience greater uptime—with user-replaceable printheads you can avoid the delay and expense of a service call.
- Automatically achieve high image quality and consistency with the HP Optical Media Advance Sensor (OMAS) and embedded spectrophotometer.
- Post-print production is easy with prints that come off the printer dry and ready—for lamination, packaging, shipping, and display.
- Minimize interruptions with pro-active alerts and the embedded Web server, which is accessible through your preferred RIP.

GO GREEN, IMPROVE YOUR OPERATOR'S WORK ENVIRONMENT


- · Provide your print operators with an improved working environment—without the health and safety considerations of printshops that use eco-solvent-based printers.
- Build a competitive edge with odorless prints⁽⁶⁾ ideal for sensitive indoor areas. HP Latex Ink prints on HP PVC-free Wall Paper meet the GREENGUARD Children & Schools standard for low emitting products⁽⁷⁾ and AgBB criteria for health-related evaluation of VOC emissions of indoor building products. (8)
- No special ventilation equipment⁽⁹⁾ or external dryer requirement helps keep energy costs down.
- Distinguish your business and attract new environmentally focused customers by offering a complete solution—including water-based HP Latex Inks and HP recyclable media. (10
- Take advantage of free, convenient HP programs for recycling Original HP 789 Ink Cartridges, Printheads, and cleaning supplies(11, as well as prints produced on HP recyclable media.(10

ecohighlights

HP DESIGNJET L25500 PRINTER SERIES

- Water-based HP Latex Inks—no hazard warning labels, no HAPs $^{\mbox{\scriptsize (I)}}$
- No special ventilation required¹² Odorless prints;¹³ printed HP wall paper meets GREENGUARD and AgBB criteria(4
- Range of recyclable HP media available, with take-back program⁽⁵⁾
- ENERGY STAR® qualified product







SAVE TIME AND EXPENSE WITH USER-REPLACEABLE PRINTHEADS

The HP Designjet L25500 Printer series is designed to save you time and money. Printheads you can replace yourself eliminate the down-time and expense of a service call. And fully-automatic printhead testing and maintenance systems eliminate time-consuming daily manual



ACHIEVE QUALITY AND CONSISTENCY WITH THE OPTICAL MEDIA ADVANCE SENSOR AND OPTICAL DROP DETECTOR

Featuring sophisticated media advance controls and automatic nozzle testing, this printer is designed to produce defect-free prints that help you avoid ink and media waste. The HP Optical Media Advance Sensor (OMAS) controls the media as it advances through the printer to minimize banding at high speeds. The Optical Drop Detector (ODD) automatically tests the drop ejection performance of every printhead nozzle to produce prints free of defects.



GET HIGH PERFORMANCE WITH HP DOUBLE SWATH TECHNOLOGY

The HP Designjet L25500 uses pairs of staggered printheads in HP Double Swath Technology for a wide (1.7 inch/43.2 mm) print swath and higher throughput. To eliminate swath-to-swath banding, the print swaths overlap each other and nozzles printing in the same scan line (top and bottom printheads) are used together.



PROACTIVELY MANAGE YOUR PRINT JOBS WITH THE EMBEDDED WEB SERVER

Accessible using your preferred web browser, the embedded Web server allows you to control print settings and monitor your printer's use of ink and media. Gain tighter control over your print jobs and prevent unnecessary ink and media waste.



ELIMINATE WAITING TIME WITH PRINTS THAT ARE COMPLETELY DRY RIGHT OFF

Win business with faster turnaround times. Prints come out of the printer completely dry, so there's no waiting before you move on to lamination, finishing, or packing for shipment.



PRINT CONTINUOUS, UNATTENDED RUNS WITH THE TAKE-UP REEL,

Improve productivity by printing continuous, unattended runs—even overnight—and on long media rolls with the media take-up reel that comes standard on both 42-inch and 60-inch models

INDOOR QUALITY

LATEX INKS

REVOLUTIONARY HP LATEX INK TECHNOLOGIES HAVE THE POWER TO CHANGE YOUR FUTURE.

Innovative HP Latex Inks produce prints with the quality and durability of eco-solvent and low-solvent ink technologies⁽²⁾ but they're water-based inks. So you get the application versatility, without the hassle associated with the environmental, health, and safety considerations of solvent-based inks.

To learn more about innovative HP Latex Ink Technologies, see: WWW.HP.COM/GO/HP_LATEX_PRINTING_TECHNOLOGIES





TECHNICAL SPECIEICATIONS

ECHNICAL SPECIFICATI	
Print speed(12	
	Up to 22.8 m²/hr (246 ft²/hr)
Media	
Handling	Roll feed, take-up reel, automatic cutter for vinyl, paper-based media, backlit polyester film, and thin banners
Types	Banners, vinyls, films, fabrics, papers, mesh with liner
Size	42-in models: 58 to 106.7-cm (23 to 42-in) rolls, up to 28 kg (61.7 lb)
	60-in models: 58 to 152.4-cm (23 to 60-in) rolls, up to 40 kg (88 lb)
Loading	Rolls up to 18 cm (7.1 in) outside diameter
Thickness	Up to 0.5 mm (19.7 mil)
Printing modes ⁽¹²	
4-pass bidirectional	22.8 m²/h (246 ft²/hr)
6-pass bidirectional	16.5 m ² /h (178 ft ² /hr)
8-pass bidirectional	10.6 m ² /h (114 ft ² /hr)
10-pass bidirectional	9.0 m ² /h (97 ft ² /hr)
12-pass bidirectional	7.6 m ² /h (81 ft ² /hr)
16-pass bidirectional	6.3 m ² /h (68 ft ² /hr)
Printing	1000 1000
Print resolution	1200 x 1200 dpi
Margins (top x bottom x left	5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)
x right) Technology	HP Thermal Inkjet
Ink types	HP Latex Inks
Ink colors	Cyan, magenta, yellow, black, light cyan, light magenta
Ink drop	12 pl
Ink cartridge size	775 ml
Printheads	6 (2 x yellow/black, 2 x cyan/light cyan, 2 x light magenta/magenta)
Nozzles	2112 per printhead (2 colors per printhead, 1056 nozzles per color)
Maximum print length	No physical limit (determined by RIP software or media roll length) ^[13]
Connectivity	
Interfaces (standard)	Gigabit Ethernet (1000Base-T)
Dimensions (w x d x h)	
Printer	42-in models: 1985 x 690 x 1370 mm (78 x 27.5 x 54 in)
	60-in models: 2465 x 690 x 1370 mm (97 x 27.5 x 54 in)
Shipping	42-in models: 2230 x 810 x 1184 mm (87.8 x 31.9 x 46.6 in)
	60-in models: 2690 x 810 x 1184 mm (105.9 x 31.9 x 46.6 in)
Weight	101 11 1/3 (055)
Printer	42-in models: 161 kg (355 lb)
	60-in models: 181 kg (399 lb)
Shipping	42-in models: 250 kg (550 lb)
Shipping	42-in models: 250 kg (550 lb) 60-in models: 310 kg (682 lb)
	42-in models: 250 kg (550 lb) 60-in models: 310 kg (682 lb)
Shipping What's in the box	60-in models: 310 kg (682 lb)
	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit,
	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation
What's in the box	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit,
What's in the box Environmental ranges	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords
What's in the box Environmental ranges Operating temperature	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F)
What's in the box Environmental ranges	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords
What's in the box Environmental ranges Operating temperature Recommended operating	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Sound pressure, active Sound pressure, standby Sound power, active	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing)
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Active	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Active	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW 60-in models: 2.6 kW
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Power consumption Maximum Active Heat dissipation	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 1.8 kW 60-in models: 2.6 kW 42-in models: 12.3 kBtu/hr
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW moximum (only when warming up) 42-in models: 12.8 kW 42-in models: 12.8 kBu/hr 60-in models: 16.4 kBtu/hr
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Power consumption Maximum Active Heat dissipation	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.2 kBW 60-in models: 1.2 kBu/hr 60-in models: 16.4 kBu/hr 60-in models: 16.4 kBu/hr
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW 60-in models: 12.3 kBtu/hr 60-in models: 12.3 kBtu/hr 60-in models: 16.4 kBtu/hr 47 watts 14-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz 47-in models: 12,1 Amax per power cord
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 42-in models: 1.8 kW maximum (only when warming up) 42-in models: 1.2 s kBu/hr 60-in models: 16.4 kBtu/hr < 72 watts 0.4 watts 42-in models: Input voltage (auto ranging) 200 to 240 VAC (10% +6%), 50/60 Hz (+/- 3 Hz), 13 A max per power cord 60-in models: Input voltage (auto ranging) 220 to 240 VAC (10% +6%), 50/60 Hz (4/- 3 Hz), 13 A max per power cord 60-in models: Input voltage (auto ranging) 220 to 240 VAC (10% +6%), 50/60 Hz (4/- 3 Hz), 13 A max per power cord
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW moximum (only when warming up) 42-in models: 1.8 kW 60-in models: 12.3 kBtu/hr 60-in models: 12.3 kBtu/hr 60-in models: 15.4 kBtu/hr 47 watts 14-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz 47-in models: 1put voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW 60-in models: 1.8 kBu/hr 60-in models: 16.4 kBtu/hr 42-in models: 13.5 kBu/hr 42-in models: 13.5 kBu/hr 60-in models: 13.5 kBu/hr
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.2 k kW 60-in models: 1.2 k kW/60-in models: 1.4 k kBu/hr 60-in models: 1.4 k kBu/hr 60-in models: 1.5 k kBu/hr 60-in models: 1.5 kBu/hr
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements Certification Safety	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW 60-in models: 12.3 kBtu/hr 60-in models: 12.3 kBtu/hr 60-in models: 16.4 kBtu/hr 47-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 13 A max per power cord USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russic (GOST), China (CCC)
Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.2 k kW 60-in models: 1.2 k kW 60-in models: 1.4 k kW/hr 60-in models: 16.4 k Btu/hr 60-in models: 16.4 k Btu/hr 60-in models: 10.3 k kW/hr 42-in models: 10.3 k kW/hr 60-in models: 10.4 k btu/hr 7 Z watts 0.4 watts 42-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 15 A max per power cord 60-in models: Input voltage (auto ranging) 220 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 15 A max per power cord USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russica (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements Certification Safety Electromagnetic	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (-13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.8 kW 60-in models: 12.3 kBu/hr 60-in models: 16.4 kBtu/hr < 72 watts 42-in models: 18-in kBu/hr 42-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz (+/· 3 Hz), 13 A max per power cord 05-in models: Input voltage (auto ranging) 220 to 240 VAC (-10% +6%), 50/60 Hz (+/· 3 Hz), 13 A max per power cord USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russic (GOST), China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Active Heat dissipation Powersave Off Power requirements Certification Safety	60-in models: 310 kg (682 lb) Printer, printheads, cleaning kit, cleaning container, ink funnel, lubrication kit, Original HP sample media, printer stand, take-up reel, user maintenance kit, maintenance & troubleshooting guide, setup poster, site guide, documentation software, power cords 15 to 30° C (59 to 86° F) 18 to 25° C (64 to 77° F) -25 to 55° C (13 to 131° F) 20 to 80% RH (non-condensing) 56 dB(A) 39 dB(A) 7.5 B(A) 5.1 B(A) 42-in models: 3.5 kW maximum (only when warming up) 60-in models: 4.8 kW maximum (only when warming up) 42-in models: 1.2 k kW 60-in models: 1.2 k kW 60-in models: 1.4 k kW/hr 60-in models: 16.4 k Btu/hr 60-in models: 16.4 k Btu/hr 60-in models: 10.3 k kW/hr 42-in models: 10.3 k kW/hr 60-in models: 10.4 k btu/hr 7 Z watts 0.4 watts 42-in models: Input voltage (auto ranging) 200 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 15 A max per power cord 60-in models: Input voltage (auto ranging) 220 to 240 VAC (-10% +6%), 50/60 Hz (+/- 3 Hz), 15 A max per power cord USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russica (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China

FOR MORE INFORMATION, VISIT OUR WEBSITE AT WWW.HP.COM/GO/DESIGNJETL25500

© Copyright 2010, 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editional errors or omissions contained herein. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks 4AA2-7664ENW, May 2010

One-year limited hardware warranty; 8-hour, 5 days a week phone support

ODDEDINIC INICODALATIONI

ORDERING INFORMATION		
Product		
CH955A	HP Designjet L25500 42-in Printer	
CH956A	HP Designjet L25500 60-in Printer	
Accessories		
CQ692A	HP Designjet L25500 42-in Printer 2-in Spindle	
CQ154A	HP Designjet L25500 42-in Printer 3-in Spindle	
CQ693A	HP Designjet L25500 60-in Printer 2-in Spindle	
CQ155A	HP Designjet L25500 60-in Printer 3-in Spindle	
Original HP printheads		
CH612A	HP 789 Yellow/Black Designjet Printhead	
CH613A	HP 789 Cyan/Light Cyan Designjet Printhead	
CH614A	HP 789 Light Magenta/Magenta Designjet Printhead	
Original HP ink cartridges		
CH615A	HP 789 775-ml Black Latex Designjet Ink Cartridge	
CH616A	HP 789 775-ml Cyan Latex Designjet Ink Cartridge	
CH617A	HP 789 775-ml Magenta Latex Designjet Ink Cartridge	
CH618A	HP 789 775-ml Yellow Latex Designjet Ink Cartridge	
CH619A	HP 789 775-ml Light Cyan Latex Designjet Ink Cartridge	
CH620A	HP 789 775-ml Light Magenta Latex Designjet Ink Cartridge	
Original HP maintenance supplies		
CH621A	HP 789 Designjet Printhead Cleaning Kit	
CH622A	HP 789 Designjet Printhead Cleaning Container	
	rinting materials	
Banners	LID LIDDE Deinfarrad Danner vor vielelenn	
	HP HDPE Reinforced Banner—recyclable ⁽¹⁾ HP Durable Frontlit Scrim Banner	
	HP Outdoor Frontlit Scrim Banner	
Self-adhesive		
Sell-duffesive	HP Air Release Adhesive Gloss Cast Vinyl	
	HP One-view Perforated Adhesive Window Vinyl	
	HP Permanent Gloss Adhesive Vinyl	
	HP Permanent Matte Adhesive Vinyl	
Polyester fabrics		
HP Heavy Textile Banner—recyclable(10		
	HP Light Textile Display Banner—new, recyclable ⁽¹⁰⁾	
	HP Wrinkle-free Flag with Liner—recyclable(10	
Papers/photo	graphic papers	
	HP PVC-free Wall Paper	
	HP White Satin Poster Paper—recyclable(10	
	HP Photo-realistic Poster Paper—recyclable(10	
	HP Blue Back Billboard Paper	
Specialty mate	erials	
	HP DuPont™ Tyvek® Banner—recyclable ⁽¹⁰	
	HP Satin Canvas	
Service and s		
US218E	3 year, Next business day, Onsite, Designjet L25500 60-inch Support	
US211E	3 year, 4 hour response 13 by 5 Onsite, Designjet L25500 60-inch Support	
US212PE	1 year, Post Warranty, Next business day, Onsite, Designjet L25500 60-inch Support	
US206PE	1 year, Post Warranty, 4 hour response 13 by 5 Onsite, Designjet L25500 60-inch Support	
US203E	3 year, Next business day, Onsite, Designjet L25500 42-inch Support	
US196E	3 year, 4 hour response 13 by 5 Onsite, Designjet L25500 42-inch Support	
US197PE	1 year, Post Warranty, Next business day, Onsite, Designjet L25500 42-inch Support	
US191PE	1 year, Post Warranty, 4 hour response 13 by 5 Onsite, Designjet L25500 42-inch Support	

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/lfprinting/materials-supplies

Software: For HP Certified third-party RIP solutions, please visit us online at:

www.hp.com/go/L25500/solutions

See Site Preparation Guide requirements to ensure complete compliance with all installation and operation requirements, safety procedures, warnings, cautions, and local regulations. Download this and other manuals from: www.hp.com/go/L25500/manuals

- 1) The HP Designiet 125500 Printer produces an extremely broad range of both outdoor and indoor applications from a single device, which surpasses the number of different applications that traditional ecosolvent printers or water-based printers can produce.

 2) HP image permanence and scratch, smudge, and water resistance estimates by HP image permanence lab. Outdoor display permanence tested occording to SAC IDSO you give HP labes, low-solvent into an arrange of media, including HP media, in a vertical display orientation in simulated nominal schools of the printer of

- 3) For Dest results, print on poyeaem rount. Into Goes the american execution of the Printer series of the Printer is subject to the HP hardware warranty.

 4) The HP printer is subject to the HP hardware warranty.

 5) Some warranty limitations apply, see the HP Performance Warranty for HP Air Release Adhesive Gloss Cast Vinyl at www.hp.com/go/HPMediaWarranties.

 6) Printers using HP Latex Infa use internal heaters to dry and cure the latex polymer film. Some substrates may have inherent odor.

 7) HP PVC few Wall Paper printed using HP Latex Infa is lated in the GREENGUARD Children & Schools Certified. The GREENGUARD Children & Schools Certified. The GREENGUARD Environmental Institute is an American National Standards Institute, IASIN] authorized standards developer that establishes acceptable indoor air standards for indoor products, environments, and buildings. See www.greenguard.org.

 8) The Committee for Health-Related Evolution of 8 building Products in Germany, including criteria for testing and an evaluation scheme for health-related evaluation of VOC emissions from building products used for application indoors.

 9) Special ventilation is not required to meet US OSHA requirements on occupational exposure to VOCs from HP Latex Infa. Special ventilation equipment installation is at the discretion of the customer—no specific HP recommendation is intended. Customers should consult state and local requirements and regulations.

- regulations.

 10) HP offers the HP Large-format Media take-back program in the U.S., Europe, and Canada (as of June 1, 2010), through which most HP recyclable signage media can be returned, availability varies. Some recyclable papers can be recycled through commonly available recycling programs. For details visit www.hp.com/recycle. Aside from this program, recycling apportunities for these products are currently only available in limited areas. Customers should consult local recycling resources for recycling lines products.

 11) In the circa 50 countries and territories in which the HP Planet Partners program operates. Program features and availability varies. Where this program is not available, and for orbar consumables not included in the program, consult the Material Safety Data Sheet (MSDS) available at www.hp.com/go/ecoddata to determine appropriate disposal.
- 12) Speed based on printing using full width (152.4 cm/60 in). Measured on an HP Designiet L25500 60 in Printer. 13) Recommended up to 30 m (100 ft).

