

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Brother MFC-9330CDW

Printing device and settings	
Test Start Date and Time	12/10/2015 12:36
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Temperature and Humidity	76 degF / 25 degC 0.0 %rH
Voltage	110V
Test End Date and Time	1/12/2016 7:50

	Item	Value
Mode and Setting	Driver Version	v269.6001.18000.0
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Mono
	Duplex B&W Settings	Mono
	Setting N set count	Application
Paper Path	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
Paper	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	Xerox / HP
	Paper Weight	20lb / 80 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
	Office Category Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	27.1	23.8
	Duplex	47.6	8.0
B&W	Simplex	27.2	23.6
	Duplex	46.5	8.0

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)		ESAT (ipm)	
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	27.35	8.77 (1 set)	17.39 (5 sets)	20.61 (27 sets)	23.88
	Simplex - Word	26.19	9.16 (1 set)	17.92 (5 sets)		23.81
	Simplex - Excel	27.71	8.66 (1 set)	17.92 (5 sets)		23.76
	Simplex - Average	27.1	8.8	17.7	20.6	23.8
	Duplex - Adobe Reader	48.71	4.92 (1 set)	6.66 (3 sets)		8.08
	Duplex - Word	46.43	5.16 (1 set)	6.74 (3 sets)		8.06
	Duplex - Excel	47.58	5.02 (1 set)	6.76 (3 sets)		8.08
	Duplex - Average	47.6	5.0	6.7		8.0
B&W mode (optional for color device)	Simplex - Adobe Reader	27.75	8.65 (1 set)	17.58 (5 sets)	20.78 (27 sets)	23.56
	Simplex - Word	26.23	9.15 (1 set)	17.79 (5 sets)		23.60
	Simplex - Excel	27.36	8.77 (1 set)	17.98 (5 sets)		23.71
	Simplex - Average	27.2	8.8	17.7	20.7	23.6
	Duplex - Adobe Reader	46.79	5.12 (1 set)	6.80 (3 sets)		8.06
	Duplex - Word	46.78	5.12 (1 set)	6.72 (3 sets)		8.02
	Duplex - Excel	45.92	5.22 (1 set)	6.74 (3 sets)		8.04
	Duplex - Average	46.5	5.1	6.7		8.0

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Brother MFC-9330CDW

Printing device and settings

Test Start Date and Time	12/10/2015 12:36
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Temperature and Humidity	76 degF / 25 degC 0.0 %rH
Voltage	110V
Test End Date and Time	1/12/2016 7:50

Item	Value	
Mode and Setting	Driver Version	v269.6001.18000.0
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Mono
	Duplex B&W Settings	Mono
	Setting N set count	Application
Paper Path	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
Paper	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	Xerox / HP
	Paper Weight	20lb / 80 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4

Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	27.7	22.5
	Duplex	47.7	7.9
B&W	Simplex	27.2	21.9
	Duplex	47.3	7.9

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4

	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
			1 set only (1 set)	1 set + 30sec (1 set)	1 set + 30sec (# of sets)	
Colour Mode	Simplex - Adobe Reader	28.08	8.54 (1 set)	16.64 (5 sets)	18.59 (26 sets)	22.52
	Simplex - Word	26.57	9.03 (1 set)	17.10 (5 sets)		22.51
	Simplex - Excel	28.16	8.52 (1 set)	16.96 (5 sets)		22.59
	Simplex - Average	27.7	8.6	16.9	18.5	22.5
	Duplex - Adobe Reader	48.08	4.98 (1 set)	6.60 (3 sets)		7.98
	Duplex - Word	47.31	5.06 (1 set)	6.66 (3 sets)		7.92
	Duplex - Excel	47.54	5.04 (1 set)	6.60 (3 sets)		7.94
	Duplex - Average	47.7	5.0	6.6		7.9
B&W mode <small>(optional for color device)</small>	Simplex - Adobe Reader	28.82	8.32 (1 set)	16.99 (5 sets)	20.15 (26 sets)	22.57
	Simplex - Word	26.23	9.15 (1 set)	16.74 (5 sets)		21.62
	Simplex - Excel	26.42	9.08 (1 set)	15.86 (4 sets)		21.54
	Simplex - Average	27.2	8.8	16.5	20.1	21.9
	Duplex - Adobe Reader	48.36	4.94 (1 set)	6.62 (3 sets)		7.92
	Duplex - Word	46.34	5.16 (1 set)	6.68 (3 sets)		7.92
	Duplex - Excel	46.98	5.10 (1 set)	6.66 (3 sets)		7.92
	Duplex - Average	47.3	5.0	6.6		7.9

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters

Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER

Brother MFC-9330CDW

Printing device and settings	
Test Start Date and Time	12/10/2015 12:36
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Default
Controller	NA
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC 26.5 %rH
Voltage	110V
Test End Date and Time	1/12/2016 7:50

Item	Value
Mode and Setting	
PDL and driver version	PCL 6
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: Letter		
FPOT from Ready (seconds)		
Color	Simplex	19.58
	Duplex	32.43
B&W	Simplex	19.53
	Duplex	31.51

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex	18.58	18.59	21.57	19.58	49 Seconds
	FPOT from Ready - Duplex	31.05	32.34	33.90	32.43	49 Seconds
	FPOT from Sleep - Simplex			32.63		63 Minutes
	Recovery Time			11.1		
	FPOT from Off - Simplex			98.91		
	Warm-up Time			77.35		
B&W Mode	FPOT from Ready - Simplex	19.69	18.22	20.69	19.53	49 Seconds
	FPOT from Ready - Duplex	30.94	31.21	32.37	31.51	49 Seconds
	FPOT from Sleep - Simplex			32.16		63 Minutes
	Recovery Time			11.5		
	FPOT from Off - Simplex			93.54		
	Warm-up Time			72.86		

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.
 - 6) Details for FPOT from Sleep are shown below.

HP Data Table

Detailed Report: LETTER							
		FPOT Avg (secs)	FPOT (secs) Iteration 1	FPOT (secs) Iteration 2	FPOT (secs) Iteration 3	Application	Delay Time
Color Mode	FPOT from Sleep	32.63	32.59	32.48	32.81	Adobe Reader	63 Minutes
	FPOT from Sleep (60 minutes) HP/Non ISO Test	32.63	32.59	32.48	32.81	Adobe Reader	63 Minutes
B&W Mode	FPOT from Sleep	32.16	32.33	32.26	31.88	Adobe Reader	63 Minutes
	FPOT from Sleep (60 minutes) HP/Non ISO Test	32.16	32.33	32.26	31.88	Adobe Reader	63 Minutes

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) DLP includes detailed iterations as data measurements may vary run to run.

Test System Parameters

Item	Value
Test System	
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
Printing Device Connection	
TCP/IP	10/1000
Software	
Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
Printing Applications	Microsoft Office 2010 SP2
Adobe Reader	Adobe Reader 10.1.4
Print Driver	PCL 6

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Brother MFC-9330CDW

Printing device and settings	
Test Start Date and Time	12/10/2015 12:36
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Default
Controller	NA
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC 26.5 %rH
Voltage	110V
Test End Date and Time	1/12/2016 7:50

Item	Value
Mode and Setting	
PDL and driver version	PCL 6
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		FPOT from Ready (seconds)
Colour	Simplex	20.51
	Duplex	33.35
B&W	Simplex	19.49
	Duplex	31.72

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B&W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex	20.53	19.42	21.57	20.51	49 Seconds
	FPOT from Ready - Duplex	32.25	33.61	34.17	33.35	49 Seconds
	FPOT from Sleep - Simplex			31.13		63 Minutes
	Recovery Time			9.6		
	FPOT from Off - Simplex			72.36		
	Warm-up Time			50.79		
B&W Mode	FPOT from Ready - Simplex	18.34	19.57	20.57	19.49	49 Seconds
	FPOT from Ready - Duplex	31.69	32.28	31.19	31.72	49 Seconds
	FPOT from Sleep - Simplex			31.24		63 Minutes
	Recovery Time			10.7		
	FPOT from Off - Simplex			80.95		
	Warm-up Time			60.38		

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B&W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.
 - 6) Details for FPOT from Sleep are shown below.

HP Data Table

Detailed Report: A4							
		FPOT Avg (secs)	FPOT (secs) Iteration 1	FPOT (secs) Iteration 2	FPOT (secs) Iteration 3	Application	Delay Time
Color Mode	FPOT from Sleep	31.13	30.65	31.61	31.14	Adobe Reader	63 Minutes
	FPOT from Sleep (60 minutes) HP/Non ISO Test	31.13	30.65	31.61	31.14	Adobe Reader	63 Minutes
B&W Mode	FPOT from Sleep	31.24	30.74	31.21	31.76	Adobe Reader	63 Minutes
	FPOT from Sleep (60 minutes) HP/Non ISO Test	31.24	30.74	31.21	31.76	Adobe Reader	63 Minutes

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B&W results, the print driver was set to "print in B/W".
 - 3) DLP includes detailed iterations as data measurements may vary run to run.

Test System Parameters

Item	Value
Test System	
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
Printing Device Connection	
TCP/IP	10/1000
Software	
Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
Printing Applications	Microsoft Office 2010 SP2
Adobe Reader	Adobe Reader 10.1.4
Print Driver	PCL 6

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER







Brother MFC-9330CDW	
---------------------	--

Machine Setup Information	
Test Start Date and Time	12/16/2015 14:54
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC, 21 %rH
Test End Date and Time:	1/11/2016 12:08

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	Xerox / HP
	Paper Weight	20lb / 80 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	20.1	23.5
B&W	18.7	23.8
Notes First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims . Exact speed varies depending on the system configuration and document.		

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	21.67	2.76	16.20 15 sets	20.87 99 sets	23.66
	B	19.82	3.02	15.78 14 sets		23.51
	C	19.03	3.15	15.77 14 sets		23.45
	D	19.80	3.02	15.79 14 sets		23.44
	Average	20.1	2.9	15.8	20.8	23.5
B&W	A	23.25	2.57	16.64 15 sets	20.74 99 sets	23.82
	B	17.08	3.51	16.64 15 sets		23.91
	C	16.99	3.52	16.61 15 sets		23.89
	D	17.24	3.47	16.83 15 sets		23.94
	Average	18.7	3.2	16.6	20.7	23.8

Notes
First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Brother MFC-9330CDW

Machine Setup Information	
Test Start Date and Time	12/16/2015 14:54
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC, 21 %rH
Test End Date and Time:	1/11/2016 12:08

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	Xerox / HP
	Paper Weight	20lb / 80 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	20.5	22.7
B&W	17.1	22.7

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	20.23	2.96	15.42 14 sets	20.02 98 sets	22.78
	B	20.16	2.97	15.40 14 sets	20.02 98 sets	22.78
	C	21.12	2.84	15.44 14 sets	20.02 98 sets	22.80
	D	20.20	2.96	15.35 14 sets	20.02 98 sets	22.69
	Average	20.5	2.9	15.4	20.0	22.7
B&W	A	16.67	3.60	15.34 13 sets	20.04 96 sets	22.69
	B	17.18	3.49	15.71 14 sets	20.04 96 sets	22.75
	C	17.25	3.47	15.74 14 sets	20.04 96 sets	22.85
	D	17.17	3.49	15.67 14 sets	20.04 96 sets	22.65
	Average	17.1	3.5	15.6	20.0	22.7

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	1/13/2016 11:53
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC 16.59 %rH
Test End Date and Time:	1/15/2016 10:14

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	Xerox / HP
Paper Weight	20lb / 80 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report

Detailed Report: LETTER

	Copying Mode	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	36.48	6.57	17.59	20.81	23.81
			(1 set)	5 sets	27 sets	
	1:2	54.31	4.40	6.24	 	8.10
(1 set)			3 sets	 		
	2:2		(1 set)	 		
B&W mode	1:1	28.53	8.41	18.01	21.19	23.74
				5 sets	27 sets	
	1:2	45.74	5.24	6.86	 	8.08
			3 sets	 		
	2:2			 		

Notes

Reports located: <http://www.hp.com/go/printerclaims>

Device does not support 2:2

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	1/13/2016 11:53
Tester	BG
Machine name/model	Brother MFC-9330CDW
Colour or B&W	Colour
FW Version	1.14 (15.04.09)
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC 16.59 %rH
Test End Date and Time:	1/15/2016 10:14
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	Xerox / HP
Paper Weight	20lb / 80 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	35.17	6.82	16.28	18.83	22.63
			(1 set)	5 sets	26 sets	
	1:2	57.38	4.18	6.12		7.94
(1 set)			3 sets			
2:2						
			(1 set)			
B&W mode	1:1	25.30	9.48	15.65	20.27	19.84
				5 sets	26 sets	
	1:2	52.19	4.58	6.40		7.96
			3 sets			
2:2						

Notes
 Reports located: <http://www.hp.com/go/printerclaims>
 Device does not support 2:2