ISO/IEC 24734 Printing Productivity Report: Office Category Full Detailed Test Report - LETTER Picoh SP 4510DN

ACOIT OF 45 TODIN	
Printing device and settings	
Test Start Date and Time	12/8/2015 13:11
Tester	BG
Machine name/model	Ricoh SP 4510DN
Colour or B&W	B&W
FW Version	Printer[1.08 / M1585756D]
Temperature and Humidity	76 degF / 25 degC, 29 %rH
Voltage	110V
Test End Date and Time	1/18/2016 15:11

	Item	Value
	Driver Version	32
Mode and	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Default
	Duplex B&W Settings	Default
Setting	Setting N set count	Application
	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
Paper	Paper Feeding	Tray 2
Path	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	Xerox / HP
Damas	Paper Weight	20lb / 80 g/m2
Paper	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary	Report:	Letter
---------	---------	--------

, ,			
Office Category Test for B&W Device		FSOT (seconds)	ESAT (ipm)
B&W	Simplex	10.3	42.3
	Duplex	18.2	37.6

- Notes

 1) All printing device and driver settings were default mode.
 2) For the BIW results, the print driver was set to "print in BIW".
 3) For more information see http://www.hp.com/go/printerclaims.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Repo						
	Office	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
	Category Test	1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30se
	Simplex - Adobe Reader		(1 set)			
	Simplex - Word		(1 set)			
	Simplex - Excel				>	
Color Mode	Simplex - Average		(1 set)			
	Duplex - Adobe Reader	N/A	N/A N/A	N/A N/A	\gg	N/A
	Duplex - Word	N/A	N/A N/A	N/A N/A	\gg	N/A
	Duplex - Excel	N/A	N/A N/A	N/A N/A		N/A
	Duplex - Average	N/A	N/A	N/A	>>	N/A
	Simplex - Adobe Reader	10.07	23.82 (1 set)	37.58 (7 sets)	40.73 (46 sets)	42.30
	Simplex - Word	10.18	23.57 (1 set)	37.98 (7 sets)		42.31
B&W mode	Simplex - Excel	10.43	23.01 (1 set)	37.78 (7 sets)	\gg	42.31
	Simplex - Average	10.3	23.4	37.7	40.7	42.3
(optional for color device)	Duplex - Adobe Reader	17.80	13.48 (1 set)	26.62 (6 sets)	>	37.62
,	Duplex - Word	18.29	13.10 (1 set)	31.42 (6 sets)	\gg	37.64
	Duplex - Excel	18.26	13.12 (1 set)	26.18 (6 sets)	\gg	37.62
	Duplex - Average	18.2	13.2	28.0	$\overline{}$	37.6

- Notes

 (1) All printing device and driver settings were default mode.

 2) For the B.W results, the print driver was set to "print in B.W".

 3) For more information see thet;//www.hp.com/gop/interclaims.

 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category Full Detailed Test Report - A4 Picoh SP 4510DN

Printing device and settings				
Test Start Date and Time	12/8/2015 13:11			
Tester	BG			
Machine name/model	Ricoh SP 4510DN			
Colour or B&W	B&W			
FW Version	Printer[1.08 / M1585756D]			
Temperature and Humidity	76 degF / 25 degC, 29 %rH			
Voltage	110V			
Test End Date and Time	1/18/2016 15:11			

	Item	Value
	Driver Version	32
Mode	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Default
and Setting	Duplex B&W Settings	Default
Setting	Setting N set count	Application
	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
Paper	Paper Feeding	Tray 2
Path	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	Xerox / HP
D	Paper Weight	20lb / 80 g/m2
Paper	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

	Summary Report: A4			
	Office Catego	ry Test for B&W Device	FSOT (seconds)	ESAT (ipm)
	B&W	Simplex	14.9	42.2
		Duplex	19.3	37.6

- Notes

 1) All printing device and driver settlings were default mode.
 2) For the BLW results, the print driver was set to "print in B\W".
 3) For more information see hitty-inww.hp.com/gorinterclaims.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Repo	ort: A4					
	Office	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
	Category Test	1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30se
	Simplex - Adobe Reader		(1 set)			
	Simplex - Word		(1 set)			
Colour	Simplex - Excel		(TSEL)		\searrow	
Mode	Simplex - Average		(1 set)		\sim	
	Duplex - Adobe Reader	N/A	N/A N/A	N/A N/A		N/A
	Duplex - Word	N/A	N/A N/A	N/A N/A	\mathbb{W}	N/A
	Duplex - Excel	N/A	N/A N/A	N/A N/A	\mathbb{W}	N/A
	Duplex - Average	N/A	N/A	N/A	\searrow	N/A
	Simplex - Adobe Reader	10.39	23.10 (1 set)	37.73 (7 sets)	39.46 (46 sets)	42.31
	Simplex - Word	15.55	15.43 (1 set)	33.67 (7 sets)	\mathbb{M}	42.07
B&W mode	Simplex - Excel	18.54	12.94 (1 set)	31.32 (7 sets)	\mathbb{M}	42.23
	Simplex - Average	14.9	17.1	34.2	39.4	42.2
(optional for color device)	Duplex - Adobe Reader	18.23	13.16 (1 set)	24.50 (6 sets)	\mathbb{M}	37.54
,	Duplex - Word	20.79	11.54 (1 set)	29.06 (7 sets)	\gg	37.76
	Duplex - Excel	18.66	12.86 (1 set)	28.32 (6 sets)	\gg	37.58
	Duplex - Average	19.3	12.5	27.2	>	37.6

- Notes

 J All printing device and driver settings were default mode.

 Provided in the B/W results, the print driver was set to "print in B/W".

 For more information see http://www.hp.com/go/printerclaims.

 Port monitor not configured to follow device if the IP address changes.

Test System Parameters				
Item	Value			
Computer	HP Compaq Elite 8300 Small Form Factor			
Processor	Intel Core i7 -3770, 3.4 GHz			
System Chip Set	Intel C216 Chipset Family SMBus Host Controller			
System Board	system devices, default system BIOS			
System Memory	4 GB			
Hard Drive Subsystem	Standard disk drive (Seagate)			
Video Subsystem	AMD Radeon HD 6350			
Optical Drive	HP DVD A DH16aCSHR ATA			
I/O Subsystem	Builtin			
USB Subsystem				
TCP/IP	TCP/IP 10/1000			
Operating System	Windows 7 64 Bit			
Printing Applications	Microsoft Office 2010			
Microsoft Office	Office 2010			
Adobe Reader	10			
Test files and location	Office category files, hard drive			

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER
Ricoh SP 4510DN

Full	DE	etan	ea	rest	керо	π -	LEI	11

Printing device and s	settings
Test Start Date and Tir	me 12/9/2015 5:54
Tester	BG
Machine name/model	Ricoh SP 4510DN
Colour or B&W	B&W
FW Version	Printer[1.08 / M1585756D]
Configuration (options)) Default
Controller	
Printing device page c	ount Not Specified
Printing supplies page	count Not Specified
Temperature and Humi	idity 76 degF / 24 degC 24.63 %rH
Voltage	110V
Test End Date and Tim	ne 1/25/2016 11:28

	Item	Value
Mode	PDL and driver version	32
and	Print Quality mode	default
	B&W settings	default
Setting	Paper feed orientation	Short Edge
D	Paper type setting	default
Paper	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)

Summary Report: Lo	etter	
		FPOT from Ready (seconds)
B&W	Simplex	6.11
	Duplex	10.42
Notes 1) All printing device and 1 2) For the B/W results, th 3) For more information si 4) Port monitor not config 5) Page counts were colle	e print driver was set to ee http://www.hp.com/g ured to follow device if t	"print in B/W". io/printerclaims. he IP address changes.

tailed Report:	LETTER					
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex					
	FPOT from Ready - Duplex					
	FPOT from Sleep - Simplex	><	><	N/A	><	
	Recovery Time	$>\!<$	><		$>\!<$	><
	FPOT from Off - Simplex	><	><		> <	><
	Warm-up Time	><	><		><	><
	FPOT from Ready - Simplex	5.74	6.22	6.36	6.11	21 Seconds
	FPOT from Ready - Duplex	10.32	10.68	10.25	10.42	21 Seconds
B&W Mode	FPOT from Sleep - Simplex	><	><	22.06	><	61 Minutes
	Recovery Time	> <	><	15.7	> <	> <
	FPOT from Off - Simplex	> <	><	33.09	> <	
	Warm-up Time	$\overline{}$		26.73	$\overline{}$	$\overline{}$

- Notes

 Ji All printing device and driver settings were default mode.

 2) For the B/W results, the print driver was set to "print in B/W".

 3) For more information see thitp://www.hp.com/go/printerclaims.

 4) Port monitor not configured to follow device if the IP address changes.

 5) Pages counts were collected after completion of the tests.

 6) Details for FPOT from Sleep are shown below.

HP Data Table)						
Detailed Report:	LETTER						
		FPOT Avg (secs)	FPOT (secs) Iteration 1	FPOT (secs) Iteration 2	FPOT (secs) Iteration 3	Application	Delay Time
Color Mode	FPOT from Sleep	N/A	N/A	N/A	N/A	Adobe Reader	
	FPOT from Sleep (60 minutes) HP/Non ISO Test	N/A	N/A	N/A	N/A	Adobe Reader	
	FPOT from Sleep	22.06	25.68	20.18	20.32	Adobe Reader	61 Minutes
B&W Mode	FPOT from Sleep (60 minutes) HP/Non ISO Test	22.06	25.68	20.18	20.32	Adobe Reader	61 Minutes

Notes

J All printing device and driver settings were default mode.

Por the B/W results, the print driver was set to "print in B/W".

DLP includes detailed iterations as data measurements may vary run to run.

	Test System Parameters		
	Item	Value	
	Computer	HP Compaq Elite 8300 Small Form Factor	
	Processor	Intel Core i7 -3770, 3.4 GHz	
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller	
	System Board	system devices, default system BIOS	
Test	System Memory	4 GB	
System	Hard Drive Subsystem	Standard disk drive (Seagate)	
	Video Subsystem	AMD Radeon HD 6350	
	Optical Drive	HP DVD A DH16aCSHR ATA	
	I/O Subsystem	Builtin	
	USB Subsystem	USB 2.0/3.0	
Printing Device Connection	TCP/IP	10/1000	
	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1	
	Drinting Applications	Microsoft Office 2010 SP2	
Software	Printing Applications	Adobe Reader 10.1.4	
	Print Driver	32	

ISO/IEC 17629 First Print Out Time Report: Office Category Full Detailed Test Report - A4

Ricoh SP 4510DN	
Printing device and settings	<u> </u>
Test Start Date and Time	12/9/2015 5:54
Tester	BG
Machine name/model	Ricoh SP 4510DN
Colour or B&W	B&W
FW Version	Printer[1.08 / M1585756D]
Configuration (options)	Default
Controller	
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 24 degC 24.63 %rH
Voltage	110V
Test End Date and Time	1/25/2016 11:28

 	Item	Value
	PDL and driver version	32
Mode	Print Quality mode	default
and	B&W settings	default
Setting	Paper feed orientation	Short Edge
Paper	Paper type setting	default
Paper	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)

Summary Report: A	4	
		FPOT from Ready (seconds)
B&W	Simplex	5.91
	Duplex	10.73
Notes 1) All printing device and 2) For the B/W results, th 3) For more information s 4) Port monitor not config 5) Page counts were colle	e print driver was set to ' ee http://www.hp.com/go ured to follow device if th	'print in B/W". /printerclaims. e IP address changes.

etailed Report:		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex					
	FPOT from Ready - Duplex					
	FPOT from Sleep - Simplex	$>\!<$	\times	N/A	><	
	Recovery Time	> <	>>		> <	><
	FPOT from Off - Simplex	$>\!<$	\times		><	\geq
	Warm-up Time	> <	\times		> <	><
	FPOT from Ready - Simplex	5.96	6.15	5.61	5.91	21 Seconds
	FPOT from Ready - Duplex	10.84	10.92	10.43	10.73	21 Seconds
B&W Mode	FPOT from Sleep - Simplex	><	\times	20.74	><	61 Minutes
	Recovery Time	> <	\times	15.1	> <	><
	FPOT from Off - Simplex	> <	\times	36.89	> <	><
	Warm-up Time	$>\!<$	\times	31.28	><	\sim

HP Data Table	9						
Detailed Report:	A4						
		FPOT Avg (secs)	FPOT (secs) Iteration 1	FPOT (secs) Iteration 2	FPOT (secs) Iteration 3	Application	Delay Time
	FPOT from Sleep	N/A	N/A	N/A	N/A	Adobe Reader	
Color Mode	FPOT from Sleep (60 minutes) HP/Non ISO Test	N/A	N/A	N/A	N/A	Adobe Reader	
	FPOT from Sleep	20.74	20.78	20.51	20.94	Adobe Reader	61 Minutes
B&W Mode	FPOT from Sleep (60 minutes) HP/Non ISO Test	20.74	20.78	20.51	20.94	Adobe Reader	61 Minutes

Notes

1) All pinnting device and driver settings were default mode.
2) For the B/W results, the print driver was set to "print in B/W".
3 DLP includes detailed iterations as data measurements may vary run to run.

	Test System Parameters				
	Item	Value			
	Computer	HP Compaq Elite 8300 Small Form Factor			
	Processor	Intel Core i7 -3770, 3.4 GHz			
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller			
Test	System Board	system devices, default system BIOS			
	System Memory	4 GB			
System	Hard Drive Subsystem	Standard disk drive (Seagate)			
-	Video Subsystem	AMD Radeon HD 6350			
	Optical Drive	HP DVD A DH16aCSHR ATA			
	I/O Subsystem	Builtin			
	USB Subsystem	USB 2.0/3.0			
Printing Device Connection	TCP/IP	10/1000			
	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1			
1	Printing Applications	Microsoft Office 2010 SP2			
Software	Finiting Applications	Adobe Reader 10.1.4			
	Print Driver	32			