



SAMSUNG

Samsung cartridge MLT-D307L (15K) Model Yield Reporting Form

Declaration of yield:

Toner cartridge yield: Average Cartridge Yield **15,000** standard pages.
Declared yield value in accordance with ISO/IEC 19752.

Average	16,710
Standard Deviation	1,159
90% Lower Confidence	15,991
90% Upper Confidence	17,428

Sample reporting form(Cartridge Yield):

Date tested : 2011/04/07 - 2011/04/11

For questions concerning testing contact:

Number of Cartridge used in testing :	9
Number of Cartridge used in calculations :	9
Type of Cartridge :	All-in-one
Shake Procedure Used?	Yes
Print mode :	Continuous (100 pages/job)
Number of Engines used in testing :	3
Media Used :	Redflagship (75g)
Paper Size :	A4
Paper feed orientation :	Short edge feed
Computer Model :	
Driver Version :	
Operating System :	
Application Software :	Acrobat Ver.9.0
Test Page Version :	Version 4.0
Power (off/on) everyday?	Yes
Daily Test break :	8 hours

Cartridge testing data :

No.	Cartridge	Engine	Temperature(°C)			Humidity (%RH)			Cartridge Yield	Cart. Used in Calculation
			Avg	Max	Min	Avg	Max	Min		
1	001	#39	22.3	23.0	21.5	51%	48%	53%	16985	Y
2	002	#40	22.8	23.5	22.0	51%	48%	53%	15574	Y
3	003	#41	22.4	22.9	21.8	51%	48%	53%	16000	Y
4	004	#39	20.8	21.5	20.1	52%	49%	54%	15529	Y
5	005	#40	22.9	23.4	22.4	52%	48%	56%	15484	Y
6	006	#41	21.8	21.0	22.6	50%	47%	53%	16171	Y
7	007	#39	21.8	21.0	22.6	50%	47%	53%	18429	Y
8	008	#40	21.8	21.0	22.6	50%	47%	53%	18210	Y
9	009	#41	21.8	21.0	22.6	50%	47%	53%	18004	Y

Printing solutions as easy as



Please visit: www.samsung.com