



## Samsung cartridge MLT-D309E(40K) Model Yield Reporting Form

Declaration of yield:

Toner cartridge yield: Average Cartridge Yield **40,000** standard pages.  
Declared yield value in accordance with ISO/IEC 19752.

Average	45379
Standard Deviation	3814
90% Lower Confidence	43015
90% Upper Confidence	47743

Sample reporting form(Cartridge Yield):

Date tested : **2011/6/13~6/21**

For questions concerning testing contact:

Number of Cartridge used in testing :	9
Number of Cartridge used in calculations :	9
Type of Cartridge :	All-in-one
Shake Procedure Used?	Yes
Print mode :	Continuous (100 pages/job)
Number of Engines used in testing :	3
Media Used :	Samsung Premium(75g)
Paper Size :	A4
Paper feed orientation :	Short edge feed
Computer Model :	
Driver Version :	
Operating System :	
Application Software :	Acrobat version 7.0
Test Page Version :	Version 4.0
Power (off/on) everyday?	Yes
Daily Test break :	8 hours

Cartridge serial numbers

1	2	3	4
5	6	7	8
9			

Engine serial numbers (Engine type : )

#1	#2	#3	#1
#2	#3	#1	#2
#3			

## Cartridge testing data :

No.	Cartridge	Engine	Temperature(°C)			Humidity (%RH)			Cartridge Yield	Cart. Used in Calculation
			Avg	Max	Min	Avg	Max	Min		
1	001	#1	22.5	23.0	22.0	54%	55%	53%	40211	Y
2	002	#2	22.5	23.0	22.0	54%	55%	53%	43619	Y
3	003	#3	22.5	23.0	22.0	54%	55%	53%	42536	Y
4	004	#1	22.9	23.5	22.3	53%	54%	52%	50245	Y
5	005	#2	22.9	23.5	22.3	53%	54%	52%	50779	Y
6	006	#3	22.9	23.5	22.3	53%	54%	52%	44384	Y
7	007	#1	22.9	23.5	22.3	53%	54%	52%	43907	Y
8	008	#2	22.9	23.5	22.3	53%	54%	52%	50751	Y
9	009	#3	22.9	23.5	22.3	53%	54%	52%	41978	Y

\*\* Due to configuration of climate control data logging system the reported temperatures are not exact.  
At no time did temperature deviate by more than 2 degrees and is within ISO specified range.

Printing solutions  
as easy as



Please visit: [www.samsung.com](http://www.samsung.com)