

Reporting Form
For Hewlett Packard LaserJet 4000/4050 – Cartridge Model C4127A

Declaration of yield:

Toner cartridge yield: Average cartridge yield 6000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average: 6818
 Standard Deviation: 288
 90% LCL: 6629

Dates Tested: 2003/12/29-2003/01/06

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations	9
Shake Procedure Used?	Yes, at 1 st and 2 nd fades
Print Mode	Continuous (100 pages/job)
Number of engines used in testing	3
Media used	Xerox 4024
Paper Size	Letter
Paper feed orientation	Short edge feed
Driver version	HP 4050 Series PCL5
Test page version	3.2
Power (off/on) everyday	No

Cartridge Testing Data

Cartridge	Lot Code	Engine	Temperature			Humidity			Cartridge Yield	Used in calculation?
			Min	Avg	Max	Min	Avg	Max		
C4127A-001	3F22U1	USQA012503	23.1	23.1	23.1	46.7	50.6	54.0	6759	Y
C4127A-002	3F22U1	USQA012503	19.1	23.1	23.6	19.2	49.7	53.1	7332	Y
C4127A-003	3F22U1	USQA012503	19.1	23.2	23.6	19.2	49.9	53.1	6831	Y
C4127A-004	2L05U2	USQC019895	23.1	23.1	23.1	46.7	50.6	54.0	6563	Y
C4127A-005	3F22U1	USQC019895	19.1	23.1	23.6	19.2	49.7	53.1	7196	Y
C4127A-006	3F22U1	USQC019895	19.1	23.2	23.6	19.2	49.9	53.1	6809	Y
C4127A-007	3F22U1	USQC019064	23.1	23.1	23.1	46.7	50.6	54.0	6439	Y
C4127A-008	3D22U2	USQC019064	19.1	23.1	23.6	19.2	49.7	53.1	6827	Y
C4127A-009	3F22U1	USQC019064	19.1	23.2	23.6	19.2	49.9	53.1	6609	Y