

HP LaserJet 4100 cartridge model C8061X Yield Reporting Form

Declaration of Yield

| |
|---|
| Toner cartridge yield: Average cartridge yield 10,000 standard pages Declared yield value in accordance with ISO/IEC 19752 |
|---|

| | |
|-----------------------------|--------|
| Average: | 10,817 |
| Standard Deviation: | 320 |
| 90% Lower confidence limit: | 10,619 |

Date tested: 03/23/2007– 04/19/2007

| | |
|---|---|
| Number of cartridges used in testing: | 9 |
| Number of cartridges used in calculation: | 9 |
| Type of cartridge: | Hewlett Packard C8061X all in one |
| Shake procedure used?: | No |
| Print mode: | Continuous, 500 page jobs up to 9,000 pages then 100 page jobs |
| Number of engines used in testing | 3 |
| Media used | HP Office |
| Paper size: | Letter |
| Paper feed orientation: | Short edge feed |
| Computer model: | Compaq Evo desktop |
| Operating system: | Windows XP |
| Application software: | Adobe Acrobat 6.0 |
| Print driver version: | HP LaserJet 4100 PCL6 |
| Connection type: | JetDirect |
| Test page version: | Version 4.0 pdf |

(filename: Download_Free___19752_Test_Chart__.pdf from ISO SC28 website)

| | |
|--------------------------|----|
| Power (off/on) everyday: | No |
|--------------------------|----|

Cartridge lot codes tested: 6H29V1k (6), 6H30V2k (3)

Engine serial numbers (Engine type: HP LaserJet 4100)

- USBNJ11673, firmware version 20030729 01.040.2
- USBNK12641, firmware version 20030729 01.040.2
- USBDF04320, firmware version 20030729 01.040.2

Cartridge testing data:

| C8061X | | LJ 4100 | Temperature, C | | | Humidity, %RH | | | |
|------------------|-----------------|---------------------|-----------------------|------------|----------------|----------------------|------------|----------------|------------------------|
| Cartridge | Lot Code | Engine SerNo | Max | Min | Average | Max | Min | Average | Cartridge Yield |
| C8061X-1 | 6H30V2k | USBNJ11673 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10800 |
| C8061X-2 | 6H29V1k | USBNK12641 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 11173 |
| C8061X-3 | 6H29V1k | USBDF04320 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10673 |
| C8061X-4 | 6H29V1k | USBNJ11673 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 11129 |
| C8061X-5 | 6H29V1k | USBNK12641 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10325 |
| C8061X-6 | 6H30V2k | USBDF04320 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 11300 |
| C8061X-7 | 6H29V1k | USBNJ11673 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10748 |
| C8061X-8 | 6H30V2k | USBNK12641 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10638 |
| C8061X-9 | 6H29V1k | USBDF04320 | 23.2 | 22.7 | 23.0 | 53.2 | 45.2 | 51.2 | 10571 |