

HP LaserJet 4350 cartridge model Q5942A Yield Reporting Form

Declaration of Yield

Toner cartridge yield: Average cartridge yield 10000 standard pages Declared yield value in accordance with ISO/IEC 19752
--

Average:	10707
Standard Deviation:	473
90% Lower confidence limit:	10414

Date tested: 2006/09/26– 2006/10/09

Number of cartridges used in testing:	9
Number of cartridges used in calculation:	9
Type of cartridge:	Hewlett Packard Q5942A all in one
Shake procedure used?:	No
Print mode:	Continuous, 300 page job up to 9000 pages Continuous, 100 page job thereafter
Number of engines used in testing	3
Media used	HP Office
Paper size:	Letter
Paper feed orientation:	Short edge feed
Computer model:	Compaq Evo Desktop
Operating system:	Windows XP
Application software:	Adobe Acrobat 7.0
Print driver version:	HP LJ4350 PCL 6
Connection type:	JetDirect
Test page version:	Version 4.0 pdf

(filename: Download_Free___19752_Test_Chart__.pdf from ISO SC28 website)

Power (off/on) everyday:	No
Cartridge lot codes tested:	6I11Z1K (3), 6I12Z1K (3), 6I09Z1K (3)

Engine serial numbers (Printer type: HP LaserJet 4350)

- CN2C489006, firmware version 20060718
- CN2C489008, firmware version 20060718
- CN2C489005, firmware version 20060718

Yield Test Report for Hewlett Packard Monochrome LaserJet Toner Cartridge tested as per ISO/IEC 19752

Cartridge testing data:

Cartridge	Lot Code	Engine SerNo	Temperature, C**			Humidity, %RH			Cartridge Yield
			Max	Min	Average	Max	Min	Average	
Q5942A-061	5J18H1K	CN2C489006	23.1	22.5	22.9	53.6	47.3	51.4	11385
Q5942A-062	5J18H1K	CN2C489008	23.1	22.5	22.9	53.6	47.3	51.4	11349
Q5942A-063	5J18H1K	CN2C489005	23.1	22.5	22.9	53.6	47.3	51.4	11171
Q5942A-064	5J18H1K	CN2C489006	23.1	22.5	22.9	53.6	47.3	51.4	10275
Q5942A-065	5J18H1K	CN2C489008	23.1	22.5	22.9	53.6	47.3	51.4	10500
Q5942A-066	5J18H1K	CN2C489005	23.1	22.5	22.9	53.6	47.3	51.4	10300
Q5942A-067	5J18H1K	CN2C489006	23.1	22.5	22.9	53.6	47.3	51.4	10206
Q5942A-068	5J18H1K	CN2C489008	23.1	22.5	22.9	53.6	47.3	51.4	10465
Q5942A-069	5J18H1K	CN2C489005	23.1	22.5	22.9	53.6	47.3	51.4	10712