

## HP LaserJet P2015 cartridge model Q7553A Yield Reporting Form

### Declaration of Yield

Toner cartridge yield: Average cartridge yield 3,000 standard pages<sup>1</sup>  
Declared yield value in accordance with ISO/IEC 19752

Average<sup>1</sup>: 3,110  
Standard Deviation: 113  
90% Lower confidence limit<sup>1</sup>: 3,040

Date tested: 9/13/2006– 9/16/2006

Number of cartridges used in testing: 9  
Number of cartridges used in calculation: 9  
Type of cartridge: Hewlett Packard Q7553A all in one  
Shake procedure used?: yes, at first and second fade  
Print mode: Continuous, 100 page job up to 2700 pages  
Continuous, 25 page job thereafter  
Number of engines used in testing 3  
Media used HP Office, 20lb  
Paper size: Letter  
Paper feed orientation: short edge feed  
Computer model: Compaq EVO desktop  
Operating system: Windows XP Professional  
Application software: Adobe Acrobat 7.0  
Print driver version: HP LaserJet P2015 PCL5e  
Connection type: JetDirect  
Test page version: Version 4.0 pdf

(filename: Download\_Free\_19752\_Test\_Chart\_.pdf from ISO SC28 website)

Power (off/on) everyday: no  
Cartridge lot codes tested: 6F29H1BK (4), 6G11H2BK (3), 6F24H1BK (2)

Engine serial numbers (Engine type: HP LaserJet P2015)

- CNBW6820Z6, firmware version 20060619
- CNBW6820XS, firmware version 20060619
- CNBW682137, firmware version 20060619

## Cartridge testing data:

LJ P2015 Q7553A		Engine serial#	Temperature, °C**			Humidity			Cartridge Yield
Cartridge	Lot Code		Max	Min	Average	Max	Min	Average	
Q7553A-001	6F29H1BK	CNBW6820Z6	23.2	22.6	22.9	55.4	46.7	51.3	3082
Q7553A-002	6F29H1BK	CNBW6820XS	23.2	22.6	22.9	55.4	46.7	51.3	2964
Q7553A-003	6G11H2BK	CNBW682137	23.2	22.6	22.9	55.4	46.7	51.3	3289
Q7553A-004	6F24H1BK	CNBW6820Z6	23.2	22.6	22.9	55.4	46.7	51.3	3165
Q7553A-005	6F29H1BK	CNBW6820XS	23.2	22.6	22.9	55.4	46.7	51.3	3019
Q7553A-006	6G11H2BK	CNBW682137	23.2	22.6	22.9	55.4	46.7	51.3	3172
Q7553A-007	6F24H1BK	CNBW6820Z6	23.2	22.6	22.9	55.4	46.7	51.3	3077
Q7553A-008	6F29H1BK	CNBW6820XS	23.2	22.6	22.9	55.4	46.7	51.3	2983
Q7553A-009	6G11H2BK	CNBW682137	23.2	22.6	22.9	55.4	46.7	51.3	3238

\*\*Due to configuration of climate control data logging system the reported temperatures are not exact. At no time did temperature deviate by more than 2 degrees and is within ISO specified range.

<sup>1</sup> In an ISO report commonly two values are listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information, visit [www.hp.com/go/learnaboutrsupplies](http://www.hp.com/go/learnaboutrsupplies).