

HP LaserJet P2015 cartridge model Q7553X Yield Reporting Form

Declaration of Yield

Toner cartridge yield: Average cartridge yield 7,000 standard pages¹
Declared yield value in accordance with ISO/IEC 19752

Average ¹ :	7,199
Standard Deviation:	287
90% Lower confidence limit ¹ :	7,021

Date tested: 9/19/2006– 9/22/2006

Number of cartridges used in testing:	9
Number of cartridges used in calculation:	9
Type of cartridge:	Hewlett Packard Q7553X all in one
Shake procedure used?:	yes, at first and second fade
Print mode:	Continuous, 100 page job up to 6300 pages Continuous, 50 page job to first fade Continuous, 25 page job thereafter
Number of engines used in testing	3
Media used	HP Office, 20lb
Paper size:	Letter
Paper feed orientation:	short edge feed
Computer model:	Compaq EVO desktop
Operating system:	Windows XP Professional
Application software:	Adobe Acrobat 7.0
Print driver version:	HP LaserJet P2015 PCL5e
Connection type:	JetDirect
Test page version:	Version 4.0 pdf

(filename: Download_Free_19752_Test_Chart_.pdf from ISO SC28 website)

Power (off/on) everyday: no
Cartridge lot codes tested: 6F14H1AK (4), 6G03H2AK (3), 6F06H1AK (2)

Engine serial numbers (Engine type: HP LaserJet P2015)

- CNBW6820Z6, firmware version 20060619
- CNBW6820XS, firmware version 20060619
- CNBW682137, firmware version 20060619

Cartridge testing data:

LJ P2015 Q7553X		Engine serial#	Temperature, °C**			Humidity			Cartridge Yield
Cartridge	Lot Code		Max	Min	Average	Max	Min	Average	
Q7553X-001	6G03H2AK	CNBW6820Z6	23.2	22.6	22.9	54.8	46.7	51.3	7168
Q7553X-002	6F14H1AK	CNBW6820XS	23.2	22.6	22.9	54.8	46.7	51.3	7220
Q7553X-003	6F14H1AK	CNBW682137	23.2	22.6	22.9	54.8	46.7	51.3	7732
Q7553X-004	6F14H1AK	CNBW6820Z6	23.2	22.6	22.9	54.8	46.7	51.3	7257
Q7553X-005	6G03H2AK	CNBW6820XS	23.2	22.6	22.9	54.8	46.7	51.3	6828
Q7553X-006	6F06H1AK	CNBW682137	23.2	22.6	22.9	54.8	46.7	51.3	7285
Q7553X-007	6F14H1AK	CNBW6820Z6	23.2	22.6	22.9	54.8	46.7	51.3	7445
Q7553X-008	6F06H1AK	CNBW6820XS	23.2	22.6	22.9	54.8	46.7	51.3	6840
Q7553X-009	6G03H2AK	CNBW682137	23.2	22.6	22.9	54.8	46.7	51.3	7016

**Due to configuration of climate control data logging system the reported temperatures are not exact. At no time did temperature deviate by more than 2 degrees and is within ISO specified range.

¹ In an ISO report commonly two values are listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information, visit www.hp.com/go/learnaboutrsupplies.