

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Canon imageCLASS MF8580Cdw

Printing device and settings		
Test Start Date and Time	2/18/2014 13:15	
Tester	KN	
Machine name/model	imageCLASS MF8580Cdw	
Colour or B&W	Colour	
FW Version	1.37/1.22	
Temperature and Humidity	77 degF / 25 degC, 18 %rH	
Voltage	110V	
Test End Date and Time	1/7/2015 11:49	

Item	Value	
Mode and Setting	Driver Version	UFR II v20.85.0.0
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black and White
	Duplex B&W Settings	Black and White
	Setting N set count	Application
Collating function	Activated (application)	
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: Letter			
	Office Category Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	26.5	21.0
	Duplex	37.8	10.5
B&W	Simplex	26.4	21.0
	Duplex	37.6	10.5

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	27.50	8.72 ( 1 set )	17.30 ( 6 sets )	19.78 ( 24 sets )	21.06
	Simplex - Word	25.46	9.42 ( 1 set )	17.45 ( 6 sets )		21.06
	Simplex - Excel	26.52	9.03 ( 1 set )	17.35 ( 6 sets )		21.06
	Simplex - Average	26.5	9.0	17.3	19.7	21.0
	Duplex - Adobe Reader	38.10	6.28 ( 1 set )	9.32 ( 5 sets )		10.58
	Duplex - Word	37.11	6.46 ( 1 set )	9.38 ( 5 sets )		10.56
	Duplex - Excel	38.01	6.30 ( 1 set )	9.34 ( 5 sets )		10.58
	Duplex - Average	37.8	6.3	9.3		10.5
B&W mode (optional for color device)	Simplex - Adobe Reader	26.41	9.09 ( 1 set )	17.38 ( 6 sets )	19.80 ( 24 sets )	21.07
	Simplex - Word	25.83	9.27 ( 1 set )	17.50 ( 6 sets )		21.07
	Simplex - Excel	26.80	8.94 ( 1 set )	17.35 ( 6 sets )		21.07
	Simplex - Average	26.4	9.1	17.4	19.8	21.0
	Duplex - Adobe Reader	37.82	6.32 ( 1 set )	9.34 ( 5 sets )		10.58
	Duplex - Word	36.93	6.48 ( 1 set )	9.38 ( 5 sets )		10.58
	Duplex - Excel	37.99	6.30 ( 1 set )	9.34 ( 5 sets )		10.58
	Duplex - Average	37.6	6.3	9.3		10.5

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

**ISO/IEC 24734 Printing Productivity Report: Office Category**

Full Detailed Test Report - A4

Canon imageCLASS MF8580Cdw

Printing device and settings	
Test Start Date and Time	2/18/2014 13:15
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
FW Version	1.37/1.22
Temperature and Humidity	77 degF / 25 degC, 18 %rH
Voltage	110V
Test End Date and Time	1/7/2015 11:49

Item	Value	
<b>Mode and Setting</b>	Driver Version	UFR II v20.85.0.0
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black and White
	Duplex B&W Settings	Black and White
	Setting N set count	Application
	Collating function	Activated (application)
<b>Paper Path</b>	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
<b>Paper</b>	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: A4			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
<b>Colour</b>	Simplex	26.6	19.9
	Duplex	38.4	10.3
<b>B&amp;W</b>	Simplex	26.3	19.9
	Duplex	38.1	10.3

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
<b>Colour Mode</b>	Simplex - Adobe Reader	26.95	8.90 ( 1 set )	16.53 ( 6 sets )	18.82 ( 23 sets )	20.00
	Simplex - Word	26.19	9.16 ( 1 set )	16.71 ( 6 sets )		20.00
	Simplex - Excel	26.59	9.02 ( 1 set )	16.63 ( 6 sets )		19.98
	Simplex - Average	26.6	9.0	16.6	18.8	19.9
	Duplex - Adobe Reader	38.76	6.18 ( 1 set )	9.08 ( 5 sets )		10.30
	Duplex - Word	37.79	6.34 ( 1 set )	9.16 ( 5 sets )		10.30
	Duplex - Excel	38.42	6.24 ( 1 set )	9.10 ( 5 sets )		10.30
	Duplex - Average	38.4	6.2	9.1		10.3
<b>B&amp;W mode</b> (optional for color device)	Simplex - Adobe Reader	26.52	9.03 ( 1 set )	16.63 ( 6 sets )	18.88 ( 23 sets )	19.98
	Simplex - Word	25.98	9.23 ( 1 set )	16.75 ( 6 sets )		20.00
	Simplex - Excel	26.40	9.09 ( 1 set )	16.66 ( 6 sets )		20.00
	Simplex - Average	26.3	9.1	16.6	18.8	19.9
	Duplex - Adobe Reader	38.24	6.26 ( 1 set )	9.10 ( 5 sets )		10.30
	Duplex - Word	37.54	6.38 ( 1 set )	9.18 ( 5 sets )		10.30
	Duplex - Excel	38.32	6.24 ( 1 set )	9.10 ( 5 sets )		10.30
	Duplex - Average	38.1	6.2	9.1		10.3

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aC SHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

**ISO/IEC 17629 First Print Out Time Report: Office Category**

Full Detailed Test Report - LETTER

Canon imageCLASS MF8580Cdw

Printing device and settings	
Test Start Date and Time	1/27/2014 16:10
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Default
Controller	Not Specified
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 24 degC, 15 %rH
Voltage	110V
Test End Date and Time	1/14/2015 2:07

Item	Value	
<b>Mode and Setting</b>	PDL and driver version	default
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
<b>Paper</b>	Paper type setting	default
	Paper feeding	Standard cassette
<b>Paper Path</b>	Paper exit	Standard exit tray
	Output orientation	default (face up or face down)
	Duplexing unit	Short Edge

**ISO First Page Out Time Summary Report: Office Category**

Summary Report: Letter		
FPOT from Ready (seconds)		
<b>Color</b>	Simplex	16.4
	Duplex	25.4
<b>B&amp;W</b>	Simplex	16.4
	Duplex	25.4

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

**ISO First Page Out Time Report: Office Category**

Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Color Mode</b>	FPOT from Ready - Simplex	16.02	16.39	16.87	16.43	50 Seconds
	FPOT from Ready - Duplex	24.89	25.47	25.96	25.44	50 Seconds
	FPOT from Sleep - Simplex			23.47		
	Recovery Time			6.6		
	FPOT from Off - Simplex			134.24		
	Warm-up Time			117.37		
<b>B&amp;W Mode</b>	FPOT from Ready - Simplex	16.03	16.39	16.66	16.36	50 Seconds
	FPOT from Ready - Duplex	25.04	25.37	25.73	25.38	50 Seconds
	FPOT from Sleep - Simplex			23.34		
	Recovery Time			6.7		
	FPOT from Off - Simplex			134.04		
	Warm-up Time			117.38		

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
<b>Test System</b>	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Built-in
	USB Subsystem	USB 2.0/3.0
<b>Printing Device Connection</b>	TCP/IP	10/1000
	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
<b>Software</b>	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4
	Print Driver	UFRII v20.85.0.0
	Test files and location	Office category files, hard drive

**ISO/IEC 17629 First Print Out Time Report: Office Category**

**Full Detailed Test Report - A4**

Canon imageCLASS MF8580Cdw

Printing device and settings	
Test Start Date and Time	1/27/2014 16:10
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Default
Controller	Not Specified
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 24 degC, 15 %rH
Voltage	110V
Test End Date and Time	1/14/2015 2:07

Item	Value	
<b>Mode and Setting</b>	PDL and driver version	default
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
<b>Paper</b>	Paper type setting	default
	Paper feeding	Standard cassette
<b>Paper Path</b>	Paper exit	Standard exit tray
	Output orientation	default (face up or face down)
	Duplexing unit	Short Edge

**ISO First Page Out Time Summary Report: Office Category**

Summary Report: A4		
FPOT from Ready (seconds)		
<b>Colour</b>	Simplex	16.6
	Duplex	25.8
<b>B&amp;W</b>	Simplex	16.5
	Duplex	25.7

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

**ISO First Page Out Time Report: Office Category**

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Colour Mode</b>	FPOT from Ready - Simplex	16.22	16.53	17.04	16.60	50 Seconds
	FPOT from Ready - Duplex	25.26	25.62	26.49	25.8	50 Seconds
	FPOT from Sleep - Simplex			23.53		
	Recovery Time			6.5		
	FPOT from Off - Simplex			134.09		
	Warm-up Time			117.05		
<b>B&amp;W Mode</b>	FPOT from Ready - Simplex	16.18	16.51	16.86	16.52	50 Seconds
	FPOT from Ready - Duplex	25.21	25.64	26.08	25.65	50 Seconds
	FPOT from Sleep - Simplex			23.53		
	Recovery Time			6.7		
	FPOT from Off - Simplex			134.09		
	Warm-up Time			117.23		

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
<b>Test System</b>	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Bulltin
	USB Subsystem	USB 2.0/3.0
<b>Printing Device Connection</b>	TCP/IP	10/1000
<b>Software</b>	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4
	Test files and location	UFR II v20.85.0.0 Office category files, hard drive

**ISO/IEC 29183 Copy Productivity Report**

Full Detailed Test Report - LETTER

Canon imageCLASS MF8580Cdw

Machine Setup Information	
Test Start Date and Time	1/28/2014 9:26
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 16 %rH
Test End Date and Time	7/21/2014 8:38

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose ColorIok / Xerox Business 4200

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	16.6	21.0
B&W	14.8	20.7

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	16.45	3.64	15.92	20.00	20.94
				15 sets	93 sets	
	B	16.73	3.58	15.97		21.07
				15 sets		
	C	16.45	3.64	15.98		21.07
				15 sets		
D	16.44	3.64	15.98		21.07	
			15 sets			
Average	16.6	3.6	15.9	20.0	21.0	
B&W	A	14.73	4.05	15.87	20.14	20.00
				15 sets	94 sets	
	B	14.71	4.07	16.22		21.06
				14 sets		
	C	14.75	4.05	16.47		21.06
				15 sets		
D	14.74	4.05	16.47		21.06	
			15 sets			
Average	14.8	4.0	16.2	20.1	20.7	

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

**ISO/IEC 29183 Copy Productivity Report**

**Full Detailed Test Report - A4**

Canon imageCLASS MF8580Cdw

**Machine Setup Information**

Test Start Date and Time	1/28/2014 9:26
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 16 %rH
Test End Date and Time	7/21/2014 8:38

	Pre-set Item	Pre-set Value
<b>Mode</b>	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
<b>Paper</b>	Paper Sending Direction	Default
	Paper Type Setting	Default
<b>Paper Path</b>	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
<b>Temporary Stop</b>	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

<b>Paper</b>	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose ColorIok / Xerox Business 4200

Summary Report: A4		
	sFCOT	sESAT (ipm)
<b>Colour</b>	17.0	19.9
<b>B&amp;W</b>	14.9	19.9

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
<b>Colour</b>	A	17.23	3.47	15.02 14 sets	19.00 88 sets	19.98
	B	16.89	3.55	15.02 14 sets		20.00
	C	16.89	3.54	15.03 14 sets		20.00
	D	16.89	3.54	15.02 14 sets		20.00
	Average	17.0	3.5	15.0	19.0	19.9
<b>B&amp;W</b>	A	14.90	4.01	15.59 14 sets	19.16 89 sets	19.98
	B	14.86	4.01	15.58 14 sets		20.00
	C	14.89	4.01	15.59 14 sets		19.98
	D	14.87	4.01	15.58 14 sets		19.98
	Average	14.9	4.0	15.5	19.1	19.9

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	1/29/2014 8:26
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 19 %rH
Test End Date and Time:	7/21/2014 12:11

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Colour for Colour and B/W for B/W
Auto Density Adjustment	Default
Collating function	Set in Control Panel
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4
Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	37.72	6.35	16.23	19.71	21.05
			( 1 set )	6 sets	26 sets	
	1:2	48.44	4.94	8.60	<del>10.58</del>	10.58
( 1 set )			5 sets	<del>5 sets</del>		
2:2	70.45	3.40	8.52	<del>10.58</del>	10.58	
		( 1 set )	5 sets	<del>5 sets</del>		
B&W mode	1:1	24.07	9.96	17.82	17.79	21.06
				6 sets	26 sets	
	1:2	42.21	5.66	9.02	<del>10.58</del>	10.58
			5 sets	<del>5 sets</del>		
2:2	44.14	5.42	8.88	<del>10.58</del>	10.58	
			5 sets	<del>5 sets</del>		

Notes  
Reports located: <http://www.hp.com/go/printerclaims>

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	1/29/2014 8:26
Tester	KN
Machine name/model	imageCLASS MF8580Cdw
Colour or B&W	Colour
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 19 %rH
Test End Date and Time:	7/21/2014 12:11

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Colour for Colour and B/W for B/W
Auto Density Adjustment	Default
Collating function	Set in Control Panel
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4
Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	38.64	6.20	15.55	16.36	19.98
			( 1 set )	6 sets	25 sets	
	1:2	49.62	4.82	8.40		10.30
( 1 set )			5 sets			
2:2	71.54	3.34	8.32		10.30	
		( 1 set )	5 sets			
B&W mode	1:1	25.35	9.46	17.01	16.96	19.98
				6 sets	25 sets	
	1:2	43.02	5.56	8.80		10.30
			5 sets			
2:2	45.19	5.30	8.66		10.30	
			5 sets			

Notes  
 Reports located: <http://www.hp.com/go/printerclaims>