ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER
Lexmark Lexmark C746dn

device and settings	
Test Start Date and Time	1/8/2015 7:42
Tester	KN
Machine name/model	Lexmark C746dn
Colour or B&W	Colour
FW Version	FHC.HSC.F260a-0
Temperature and Humidity	74 degF / 23 degC, 20 %rH
Voltage	110V
Test End Date and Time	1/14/2015 12:24

	Item	Value	
	Driver Version	PS3 v6.1.7601.17514	
Mode	Media/Quality Setting	Default / Default	
and	Simplex B&W Settings	Print in black and white	
Setting	Duplex B&W Settings	Print in black and white	
Setting	Setting N set count	Application	
	Collating function	Activated (application)	
	Paper Sending Direction	Default	
	Paper Size Setting	Default	
Paper	Paper Feeding	Tray 2	
Path	Paper Exit	Standard Exit Tray	
	Output Orientation	Default (face down)	
	Duplexing Unit (Yes/No)	Yes	
	Paper Manufacturer	HP/Xerox	
Paper	Paper Weight	20lb / 75 g/m2	
	Paper Size	letter/A4	
		HP Multipurpose Colorlok / Xerox Business 4200	

Summary Report: Lette	F		
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Color	Simplex	16.0	35.3
Color	Duplex	19.7	23.1
B&W	Simplex	15.9	35.3
Daw	Duplex	19.7	23.1

- Notes
 1) All printing device and driver settings were default mode.
 2) For the BIW results, the print driver was set to "print in BIW".
 3) For more information see http://www.pb.com/go/printerciaims.
 4) Port monitor not configured to follow device if the IP address chang

Detailed Repo	rt: LETTER					
	Office	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
	Category Test	1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
	Simplex - Adobe Reader	16.27	14.73 (1 set)	28.64 (6 sets)	33.84 (39 sets)	35.36
	Simplex - Word	15.69	15.29 (1 set)	28.94 (6 sets)		35.40
	Simplex - Excel	16.01	14.98 (1 set)	28.80 (6 sets)	\gg	35.36
Color Mode	Simplex - Average	16.0	15.0	28.7	33.8	35.3
	Duplex - Adobe Reader	19.97	12.00 (1 set)	19.48 (5 sets)	\gg	23.16
	Duplex - Word	19.54	12.26 (1 set)	19.70 (5 sets)	>	23.14
	Duplex - Excel	19.57	12.26 (1 set)	19.70 (5 sets)		23.18
	Duplex - Average	19.7	12.1	19.6	>>	23.1
	Simplex - Adobe Reader	15.91	15.07 (1 set)	28.81 (6 sets)	33.89 (39 sets)	35.33
	Simplex - Word	15.75	15.23 (1 set)	29.03 (6 sets)		35.47
B&W mode	Simplex - Excel	15.92	15.07 (1 set)	28.88 (6 sets)	\gg	35.39
	Simplex - Average	15.9	15.1	28.9	33.8	35.3
(optional for color device)	Duplex - Adobe Reader	19.68	12.18 (1 set)	19.62 (5 sets)	>	23.18
	Duplex - Word	19.57	12.24 (1 set)	19.70 (5 sets)	>	23.20
	Duplex - Excel	19.64	12.20 (1 set)	19.66 (5 sets)	\geqslant	23.20
	Duplex - Average	19.7	12.2	19.6	\sim	23.1

- Notes

 1) All printing device and driver settings were default mode.

 2) For the B/W results, the print driver was set to "print in B/W".

 3) For more information see hittp://www.hp.com/go/printerclaims.

 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters			
Item	Value		
Computer	HP Compaq Elite 8300 Small Form Factor		
Processor	Intel Core i7 -3770, 3.4 GHz		
System Chip Set	Intel C216 Chipset Family SMBus Host Controller		
System Board	system devices, default system BIOS		
System Memory	4 GB		
Hard Drive Subsystem	Standard disk drive (Seagate)		
Video Subsystem	AMD Radeon HD 6350		
Optical Drive	HP DVD A DH16aCSHR ATA		
I/O Subsystem	Builtin		
USB Subsystem	USB 2.0/3.0		
TCP/IP	TCP/IP 10/1000		
Operating System	Windows 7 64 Bit		
Printing Applications	Microsoft Office 2010		
Microsoft Office	Office 2010		
Adobe Reader	10		
Test files and location	Office category files, hard drive		

ISO/IEC 24734 Printing Productivity Report: Office Category Full Detailed Test Report - A4 Lexmark Lexmark C746dn

KN
Lexmark C746dn
Colour
FHC.HSC.F260a-0
74 degF / 23 degC, 20 %rH
110V
1/14/2015 12:24

	ltem	Value
		PS3 v6.1.7601.17514
	Media/Quality Setting	Default / Default
Mode	Simplex B&W Settings	Print in black and white
and	Duplex B&W Settings	Print in black and white
Setting	Setting N set count	Application
	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
Paper	Paper Feeding	Tray 2
Path	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	HP/Xerox
Paper		20lb / 75 g/m2
гареі	Paper Size	letter/A4
	Paper type/name	HP Multipurpose Colorlok / Xerox Business 4200

Summary Report: A4			
Office Catego	ory Test for Color Device	FSOT (seconds)	ESAT (ipm)
Colour	Simplex	16.4	33.8
	Duplex	20.2	22.5
B&W	Simplex	16.3	33.7
DOW	Duplex	20.0	22.5

Notes

1) All pinting device and driver settings were default mode.
2) For the B/W results, the print driver was set to 'print in B/W'.
3) For more information see http://www.hp.com/go/printerclaims.
4) Port monitor not configured to follow device if the IP address changes.

Detailed Repo	ort: A4					
	Office	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
	Category Test	1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
	Simplex - Adobe Reader	16.55	14.48 (1 set)	27.69 (6 sets)	32.15 (37 sets)	33.86
	Simplex - Word	16.20	14.80 (1 set)	27.85 (6 sets)	\Rightarrow	33.82
Colour	Simplex - Excel	16.38	14.64 (1 set)	27.73 (6 sets)	\approx	33.72
Mode	Simplex - Average	16.4	14.6	27.7	32.1	33.8
	Duplex - Adobe Reader	20.48	11.70 (1 set)	18.28 (4 sets)	\sim	22.54
	Duplex - Word	20.04	11.96 (1 set)	19.18 (5 sets)	\gg	22.56
	Duplex - Excel	20.01	11.98 (1 set)	18.48 (4 sets)		22.56
	Duplex - Average	20.2	11.8	18.6	> <	22.5
	Simplex - Adobe Reader	16.21	14.79 (1 set)	27.77 (6 sets)	31.84 (37 sets)	33.72
	Simplex - Word	16.07	14.93 (1 set)	27.85 (6 sets)		33.67
B&W mode	Simplex - Excel	16.41	14.62 (1 set)	27.79 (6 sets)	>	33.77
	Simplex - Average	16.3	14.7	27.8	31.8	33.7
(optional for color device)	Duplex - Adobe Reader	19.93	12.02 (1 set)	19.18 (5 sets)	\gg	22.56
	Duplex - Word	19.82	12.10 (1 set)	19.20 (5 sets)	>	22.52
	Duplex - Excel	19.98	11.98 (1 set)	19.20 (5 sets)	\gg	22.56
	Duplex - Average	20.0	12.0	19.1	> <	22.5

Notes
1) All printing device and driver settings were default mode.
2) For the B/W results, the print driver was set to "print in B/W".
3) For more information see http://www.hp.com/go/printerclaims.
4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters				
Item	Value			
Computer	HP Compaq Elite 8300 Small Form Factor			
Processor	Intel Core i7 -3770, 3.4 GHz			
System Chip Set	Intel C216 Chipset Family SMBus Host Controller			
	system devices, default system BIOS			
System Memory	4 GB			
Hard Drive Subsystem	Standard disk drive (Seagate)			
	AMD Radeon HD 6350			
Optical Drive	HP DVD A DH16aCSHR ATA			
I/O Subsystem	Builtin			
USB Subsystem				
TCP/IP	TCP/IP 10/1000			
Operating System	Windows 7 64 Bit			
Printing Applications	Microsoft Office 2010			
Microsoft Office	Office 2010			
Adobe Reader	10			
Test files and location	Office category files, hard drive			

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER
Lexmark Lexmark C746dn

Printing device and settings	
Test Start Date and Time	1/8/2015 7:42
Tester	KN
Machine name/model	Lexmark C746dn
Colour or B&W	Colour
Configuration (options)	Default
Controller	LHSC.CM.E238-0
Printing device page count	19282
Printing supplies page count	Not Specified
Temperature and Humidity	73 degF / 23 degC, 21 %rH
Voltage	110V
Test End Date and Time	2/2/2015 9:19
*	

	Item	Value
Mode	PDL and driver version	PS3 v6.1.7601.17514
and	Print Quality mode	default
Setting	B&W settings	default
Setting	Paper feed orientation	Short Edge
Daman	Paper type setting	default
Paper	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)
	Duplexing unit	Short Edge

ISO First Page Out Time Summary Report: Office Category

Summary Report: Le	etter	
		FPOT from Ready (seconds)
Color	Simplex	10.8
Color	Duplex	16.3
B&W	Simplex	10.6
	Duplex	16.2

- Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to 'print in B/W'.
 3) For more information see http://www.hp.com/go/printerclaims.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category						
Detailed Report:	LETTER					
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
	FPOT from Ready - Simplex	10.65	10.81	11.05	10.84	50 Seconds
	FPOT from Ready - Duplex	16.12	16.14	16.57	16.28	50 Seconds
Color Mode	FPOT from Sleep - Simplex	><	><	22.76	><	
	Recovery Time	> <	> <	11.7	> <	> <
	FPOT from Off - Simplex	> <	> <	97.41	> <	> <
	Warm-up Time			86.36		
	FPOT from Ready - Simplex	10.44	10.71	10.70	10.62	50 Seconds
	FPOT from Ready - Duplex	16.11	16.25	16.25	16.21	50 Seconds
B&W Mode	FPOT from Sleep - Simplex	><	><	21.74	><	
	Recovery Time	> <		11.0	> <	><
	FPOT from Off - Simplex	> <		80.84	> <	><
	Warm-up Time	> <	><	70.14	> <	><

- Notes

 1) All printing device and driver settings were default mode.
 2) For the BIW results, the print driver was set to "print in BIW".
 3) For more information see http://www.hp.com/go/printerclaims.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

	Test System Parameters					
	Item	Value				
	Computer	HP Compaq Elite 8300 Small Form Factor				
	Processor	Intel Core i7 -3770, 3.4 GHz				
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller				
	System Board	system devices, default system BIOS				
Test	System Memory	4 GB				
System	Hard Drive Subsystem	Standard disk drive (Seagate)				
-	Video Subsystem	AMD Radeon HD 6350				
	Optical Drive	HP DVD A DH16aCSHR ATA				
	I/O Subsystem	Builtin				
	USB Subsystem	USB 2.0/3.0				
Printing Device Connection	TCP/IP 10/1000					
	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1				
	Drinting Applications	Microsoft Office 2010 SP2				
Software	Printing Applications	Adobe Reader 10.1.4				
	Print Driver	PS3 v6.1.7601.17514				
	Test files and location	Office category files, hard drive				

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Lexmark Lexmark C746dn

Printing device and settings	Printing device and settings		
Test Start Date and Time	1/8/2015 7:42		
Tester	KN		
Machine name/model	Lexmark C746dn		
Colour or B&W	Colour		
Configuration (options)	Default		
Controller	LHSC.CM.E238-0		
Printing device page count	19282		
Printing supplies page count	Not Specified		
Temperature and Humidity	73 degF / 23 degC, 21 %rH		
Voltage	110V		
Test End Date and Time	2/2/2015 9:19		

	Item	Value
Mode	PDL and driver version	PS3 v6.1.7601.17514
and	Print Quality mode	default
Setting	B&W settings	default
Setting	Paper feed orientation	Short Edge
Paper	Paper type setting	default
гареі	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)
	Duplexing unit	Short Edge

ISO First Page Out Time Summary Report: Office Category

	FPOT from Ready (seconds)
Simplex	10.9
Duplex	16.6
Simplex	10.7
Duplex	16.4
	Simplex Duplex Simplex

Notes

J All printing device and driver settings were default mode.

J For the B/W results, the print driver was set to "print in B/W".

J For more information see http://www.hp.com/go/printerclaims.

J Pot more in rot configured to follow device it the IP address changes.

J Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category						
Detailed Report:	A4					
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
	FPOT from Ready - Simplex	10.67	10.87	11.11	10.89	50 Seconds
	FPOT from Ready - Duplex	16.50	16.48	16.94	16.64	50 Seconds
Colour Mode	FPOT from Sleep - Simplex	><	><	22.94	><	
	Recovery Time	><	><	11.8	$>\!<$	\times
	FPOT from Off - Simplex	$>\!\!<$	><	91.24	$>\!\!<$	\times
	Warm-up Time	><	><	80.13	$>\!\!<$	\times
	FPOT from Ready - Simplex	10.61	10.80	10.77	10.73	50 Seconds
	FPOT from Ready - Duplex	16.28	16.41	16.45	16.38	50 Seconds
B&W Mode	FPOT from Sleep - Simplex	><	><	22.94	><	
	Recovery Time	> <	> <	12.2	> <	>>
	FPOT from Off - Simplex	> <	> <	81.55	> <	> <
	Warm-up Time	> <	> <	70.78	> <	> <

Notes

1) All printing device and driver settings were default mode.
2) For the B/W results, the print driver was set to "print in B/W".
3) For more information see http://www.hp.com/go/printerclaims.
4) Port monitor not configued to follow device if the Pladdress changes.
5) Page counts were collected after completion of the tests.

	Test System Parameters					
	Item	Value				
	Computer	HP Compaq Elite 8300 Small Form Factor				
Processor System Chip Set		Intel Core i7 -3770, 3.4 GHz				
		Intel C216 Chipset Family SMBus Host Controller				
	System Board	system devices, default system BIOS				
Test	System Memory	4 GB				
System	Hard Drive Subsystem	Standard disk drive (Seagate)				
	Video Subsystem	AMD Radeon HD 6350				
	Optical Drive	HP DVD A DH16aCSHR ATA				
	I/O Subsystem	Builtin				
	USB Subsystem	USB 2.0/3.0				
Printing						
Device	TCP/IP	10/1000				
Connection						
	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1				
	Printing Applications	Microsoft Office 2010 SP2				
Software	Filling Applications	Adobe Reader 10.1.4				
	Print Driver	PS3 v6.1.7601.17514				
	Test files and location	Office category files, hard drive				