



USE



i n v e n t

hp embedded web server

hp LaserJet 2300

hp color LaserJet 2500

hp LaserJet 4100mfp

hp LaserJet 4200

hp LaserJet 4300

hp color LaserJet 4600

hp color LaserJet 5500

hp LaserJet 9000mfp

hp embedded web server

user guide

Configuration Page

Use the Configuration page to view current product settings, help troubleshoot printer problems, and verify the installation of optional accessories, such as dual inline memory modules (DIMMs) or paper-handling devices. The following illustration and table describe how to use this page.

HP Color LaserJet XXXX / 15.62.66.172

Information | Settings | Networking

1 Configuration Page

2 Device Information

Product Name:	HP Color LaserJet XXXX
Printer Name:	EWS LaserJet XXXX
Printer Model:	G9656A
Printer Serial Number:	MT60261174
Firmware Datecode:	20021217 04.009.0
Service ID:	00000
PS Wait Time-out:	300 seconds
Page Count:	10926
Color Page Count:	9812

3 Installed Personalities and Options

PCL	(20010402)
PCLXL	(20010402)
POSTSCRIPT	(20010402)
DIMM Slot 1:	Side 1: 16 MB Flash Side 2: 0 MB SDRAM
DIMM Slot 2:	Side 1: 128 MB SDRAM Side 2: Empty
DIMM Slot 3:	Side 1: 128 MB SDRAM Side 2: Empty
DIMM Slot 4:	Empty
DIMM Slot 5:	Empty
EIO1:	HP JetDirect J6057A
EIO2:	Empty
EIO3:	HP J6054B
DISK Storage:	9462 MB Capacity

4 Memory

Total Memory:	256 MB
DWS:	86.0
Automatic Resource Saving Enabled	

5 Security

Control Panel Lock:	NONE
Control Panel Password:	DISABLED
Device Type: DISK	Write Protect: DISABLED

6 Paper Trays and Options

Default Paper Size:	LETTER
Tray 1 Size:	ANY SIZE
Tray 1 Type:	ANY
Tray 2 Size:	11X17
Tray 2 Type:	PLAIN
Tray 3 Size:	LEGAL
Tray 3 Type:	PLAIN
Tray 4 Size:	LETTER
Tray 4 Type:	PLAIN
Duplex Unit	

Note: See the table on the following page for information about the callouts.

Internal:

- Input Trays:
- 1: TRAY 1, 100 Sheets
 - 2: TRAY 2, 500 Sheets
 - 3: TRAY 3, 500 Sheets
 - 4: TRAY 4, 500 Sheets
- Output Bins:
- 1: STANDARD_OUTPUT, 500 Sheets, Face Down

