

# HP Photosmart R-series dock



Fast and easy—connect HP Photosmart R-series digital cameras to your computer for transferring, printing and sharing of digital photos and video using the HP Photosmart R-series dock. Dock your camera and charge up to two lithium ion batteries—one in your HP camera and one in the dock's spare battery bay. Transfer photos easily to your PC, send photo e-mails via HP Instant Share or print at the touch of a button.

## Charge two camera batteries

- Recharge two batteries—one in-camera and included spare—using extra battery bay

## Easy, one-touch operation

- Transfer photos to PC, plus easily e-mail and print with two easy-touch buttons

## View slideshows on TV

- Run photo slideshows from the camera's memory on TV—remote control included

## Always connected

- Always connected—avoid having to re-connect PC cables every time you download

## Ready-to-go

- Store camera in it's dock so it's ready to go when you are



## One-step to print

- Easily print photos—without a computer—directly from your docked camera to HP Photosmart printers and select HP all-in-ones via included USB cable. The dock supports PictBridge for worry-free photo printing.

## Stylish design

- Eye-catching design complements your HP Photosmart R-series digital camera

## Easy connection and support

- Works easily with USB compatible PC and Mac®
- 90-day limited warranty backed by HP's 24-hour, 7-days-a-week Customer Care service and support
- HP Customer Care, including 24-hour web support at [www.hp.com/go/support](http://www.hp.com/go/support)

# HP Photosmart R-series dock

## Technical specifications

<b>Panel Buttons</b>	TV button, printer or PC button
<b>External I/O Ports</b>	USB A (printer), USB B (PC), A/V, power
<b>Connectivity</b>	USB (compatible with USB 2.0 specifications)
<b>Compatibility</b>	For use with HP Photosmart R-series cameras

<b>Dimensions (w x d x h)/weight</b>	5.12 x 2.13 x 1.26 in. dock only (130 x 54 x 32 mm)/3.84 oz dock with insert (108g), 1.26 oz remote with battery (35.8g)
<b>Operating environment</b>	Operating temperature (maximum/recommended): 41 to 113° F (5 to 45° C); humidity range (recommended operating): 15 to 85% RH
<b>Power supply:</b>	Universal AC adapter: 100 - 240 VAC (+/-10%), 50/60 Hz (+/- 3 Hz) input, 3.7 VDC, 2.5 amp output
<b>Power consumption:</b>	8.25 watts maximum (when charging the secondary bay at full current if camera is also charging its battery at full current)
<b>Warranty</b>	90-day limited warranty backed by HP customer care service and support; HP Customer Support including 24-hour web support, at <a href="http://www.hp.com/support">www.hp.com/support</a>

## Ordering information

### What's in the box?

HP Photosmart R-series dock; HP Photosmart 3.3V AC adapter; HP photosmart R07 rechargeable lithium ion battery; A/V cable for connecting dock to TV; remote control; battery for remote control; user's manual; warranty and regulatory brochure; USB cable for connecting dock to PC; dock inserts for HP R-series cameras

### Product number

C8887A

### HP product

HP Photosmart R-series camera dock

### Optional accessories

L1810A  
L1811A  
L1812A

HP Photosmart quick recharge kit  
HP Photosmart premium leather camera case for R-series cameras  
HP Photosmart R07/rechargeable lithium ion battery for HP R-series cameras



Energy Star and the Energy Star logo are U.S. registered marks of the United States Environmental Protection Agency.

© 2003 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information visit our website at [www.hp.com](http://www.hp.com)

