

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Brother MFC-L8600CDW

Printing device and settings		
Test Start Date and Time	6/19/2015 16:57	
Tester	AH	
Machine name/model	Brother MFC-L8600CDW	
Colour or B&W	Colour	
FW Version	D1405282148	
Temperature and Humidity	74 degF / 24 degC, 30 %rH	
Voltage	110V	
Test End Date and Time	6/23/2015 11:24	

Item	Value	
Mode and Setting	Driver Version	1.02.00 (07 Nov 2013)
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	mono
	Duplex B&W Settings	mono
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
	Office Category Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	17.4	31.0
	Duplex	26.2	15.3
B&W	Simplex	16.5	30.9
	Duplex	24.9	15.3

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	18.28	13.12 (1 set)	25.03 (6 sets)		31.24
	Simplex - Word	16.96	14.14 (1 set)	25.64 (6 sets)		30.92
	Simplex - Excel	16.88	14.20 (1 set)	25.67 (6 sets)		31.05
	Simplex - Average	17.4	13.8	25.4		31.0
	Duplex - Adobe Reader	27.24	8.80 (1 set)	12.92 (4 sets)		15.38
	Duplex - Word	25.46	9.42 (1 set)	13.26 (4 sets)		15.40
	Duplex - Excel	25.84	9.28 (1 set)	13.24 (4 sets)		15.36
	Duplex - Average	26.2	9.1	13.1		15.3
B&W mode (optional for color device)	Simplex - Adobe Reader	17.19	13.96 (1 set)	25.68 (6 sets)	N/A	30.96
	Simplex - Word	16.26	14.75 (1 set)	26.02 (6 sets)		30.92
	Simplex - Excel	15.88	15.10 (1 set)	26.14 (6 sets)		30.96
	Simplex - Average	16.5	14.6	25.9	N/A	30.9
	Duplex - Adobe Reader	25.11	9.54 (1 set)	13.32 (4 sets)		15.38
	Duplex - Word	24.90	9.62 (1 set)	13.46 (4 sets)		15.38
	Duplex - Excel	24.46	9.80 (1 set)	13.50 (4 sets)		15.38
	Duplex - Average	24.9	9.6	13.4		15.3

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aC SHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/100
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Brother MFC-L8600CDW

Printing device and settings		
Test Start Date and Time	6/19/2015 16:57	
Tester	AH	
Machine name/model	Brother MFC-L8600CDW	
Colour or B&W	Colour	
FW Version	D1405282148	
Temperature and Humidity	74 degF / 24 degC, 30 %rH	
Voltage	110V	
Test End Date and Time	6/23/2015 11:24	

Item	Value	
Mode and Setting	Driver Version	1.02.00 (07 Nov 2013)
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	mono
	Duplex B&W Settings	mono
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4

Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	18.1	29.4
	Duplex	26.2	15.0
B&W	Simplex	16.8	29.3
	Duplex	24.9	15.1

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4

	Office Category Test	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Colour Mode	Simplex - Adobe Reader	19.01	12.62 (1 set)	23.05 (5 sets)		29.42
	Simplex - Word	17.62	13.62 (1 set)	23.77 (5 sets)		29.35
	Simplex - Excel	17.61	13.62 (1 set)	23.78 (5 sets)		29.49
	Simplex - Average	18.1	13.2	23.5		29.4
	Duplex - Adobe Reader	27.13	8.84 (1 set)	12.80 (4 sets)		15.08
	Duplex - Word	25.65	9.34 (1 set)	13.04 (4 sets)		15.08
	Duplex - Excel	25.53	9.38 (1 set)	13.02 (4 sets)		15.08
	Duplex - Average	26.2	9.1	12.9		15.0
B&W mode (optional for color device)	Simplex - Adobe Reader	17.05	14.07 (1 set)	23.95 (5 sets)	N/A	29.42
	Simplex - Word	16.63	14.42 (1 set)	24.31 (5 sets)		29.49
	Simplex - Excel	16.66	14.39 (1 set)	24.25 (5 sets)		29.18
	Simplex - Average	16.8	14.2	24.1	N/A	29.3
	Duplex - Adobe Reader	25.23	9.50 (1 set)	13.02 (4 sets)		15.10
	Duplex - Word	24.74	9.70 (1 set)	13.26 (4 sets)		15.10
	Duplex - Excel	24.67	9.72 (1 set)	13.30 (4 sets)		15.10
	Duplex - Average	24.9	9.6	13.1		15.1

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters

Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER

Brother MFC-L8600CDW

Printing device and settings	
Test Start Date and Time	6/19/2015 16:57
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	73 degF / 23 degC, 30 %RH
Voltage	110V
Test End Date and Time	8/6/2015 11:46

Item	Value
Mode and Setting	
PDL and driver version	1.02.00 (07 Nov 2013)
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: Letter		
		FPO from Ready (seconds)
Color	Simplex	11.68
	Duplex	21.05
B&W	Simplex	10.42
	Duplex	19.68

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category						
Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPO from Ready - Simplex	11.18	11.11	12.75	11.68	49 Seconds
	FPO from Ready - Duplex	20.50	20.67	21.96	21.05	49 Seconds
	FPO from Sleep - Simplex			30.07		63 Minutes
	Recovery Time			17.3		
	FPO from Off - Simplex			70.38		
	Warm-up Time			57.63		
B&W Mode	FPO from Ready - Simplex	10.13	10.12	11.01	10.42	49 Seconds
	FPO from Ready - Duplex	19.20	19.51	20.32	19.68	49 Seconds
	FPO from Sleep - Simplex			29.17		63 Minutes
	Recovery Time			18.2		
	FPO from Off - Simplex			105.43		
	Warm-up Time			94.42		

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection		
TCP/IP	10/1000	
Software		
Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1	
Printing Applications	Microsoft Office 2010 SP2	
Adobe Reader	10.1.4	
Print Driver	1.02.00 (07 Nov 2013)	

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Brother MFC-L8600CDW

Printing device and settings	
Test Start Date and Time	6/19/2015 16:57
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	73 degF / 23 degC, 30 %RH
Voltage	110V
Test End Date and Time	8/6/2015 11:46

Item	Value
Mode and Setting	
PDL and driver version	1.02.00 (07 Nov 2013)
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		
		F POT from Ready (seconds)
Colour	Simplex	11.87
	Duplex	13.39
B&W	Simplex	10.58
	Duplex	12.10

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Colour Mode	F POT from Ready - Simplex	11.24	11.45	12.90	11.87	49 Seconds
	F POT from Ready - Duplex	12.97	12.82	14.37	13.39	49 Seconds
	F POT from Sleep - Simplex			30.44		63 Minutes
	Recovery Time			17.5		
	F POT from Off - Simplex			103.28		
	Warm-up Time			90.38		
B&W Mode	F POT from Ready - Simplex	10.41	10.30	11.03	10.58	49 Seconds
	F POT from Ready - Duplex	11.76	11.92	12.62	12.1	49 Seconds
	F POT from Sleep - Simplex			29.27		63 Minutes
	Recovery Time			18.2		
	F POT from Off - Simplex			57.02		
	Warm-up Time			45.99		

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection	TCP/IP	10/1000
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4 1.02.00 (07 Nov 2013)

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER

Brother MFC-L8600CDW

Machine Setup Information	
Test Start Date and Time	6/25/2015 11:54
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Not Specified
Temperature and Humidity	73 degF / 23 degC, 41 %rH
Test End Date and Time	6/29/2015 16:36

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Parameter	Value
	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	13.6	30.9
B&W	11.6	31.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	13.65	4.39	23.09 18 sets	23.86 99 sets	30.98
	B	13.62	4.40	23.15 18 sets		31.01
	C	13.54	4.42	23.07 18 sets		30.94
	D	13.59	4.41	23.11 18 sets		31.02
	Average	13.6	4.4	23.1	23.8	30.9
B&W	A	11.52	5.20	23.64 18 sets	24.26 99 sets	31.22
	B	11.54	5.19	23.56 18 sets		31.12
	C	11.51	5.20	23.43 18 sets		30.94
	D	11.47	5.22	23.46 18 sets		30.94
	Average	11.6	5.2	23.5	24.2	31.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Brother MFC-L8600CDW

Machine Setup Information	
Test Start Date and Time	6/25/2015 11:54
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Not Specified
Temperature and Humidity	73 degF / 23 degC, 41 %rH
Test End Date and Time:	6/29/2015 16:36

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	13.9	29.4
B&W	11.6	29.6

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	13.91	4.30	22.20 18 sets	22.89 99 sets	29.40
	B	13.93	4.30	21.99 17 sets		29.63
	C	13.81	4.34	21.91 17 sets		29.45
	D	13.85	4.33	21.88 17 sets		29.44
	Average	13.9	4.3	21.9	22.8	29.4
B&W	A	11.58	5.17	22.29 17 sets	23.30 99 sets	29.51
	B	11.54	5.19	22.32 17 sets		29.48
	C	11.58	5.18	22.94 18 sets		30.14
	D	11.59	5.17	22.22 17 sets		29.38
	Average	11.6	5.1	22.4	23.3	29.6

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

ISO/IEC 24735 Copy Productivity Report
 Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	6/30/2015 11:34
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Not Specified
Temperature and Humidity	74 degF / 23 degC, 57 %rH
Test End Date and Time	6/30/2015 15:56
Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	20.60	11.64 (1 set)	24.63 6 sets	23.74 34 sets	30.94
	1:2	33.90	7.06 (1 set)	11.94 4 sets		15.46
	2:2					
B&W mode	1:1	18.61	12.88	24.95 6 sets	24.19 34 sets	30.86
	1:2	31.56	7.60	12.28 4 sets		15.42
	2:2					
Notes						
Reports located: http://www.hp.com/go/printerclaims						

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	6/30/2015 11:34
Tester	AH
Machine name/model	Brother MFC-L8600CDW
Colour or B&W	Colour
FW Version	D1405282148
Configuration (options)	Not Specified
Temperature and Humidity	74 degF / 23 degC, 57 %rH
Test End Date and Time	6/30/2015 15:56

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	21.26	11.28	22.93	22.52	29.34
			(1 set)	5 sets	32 sets	
	1:2	34.43	6.96	11.68	4 sets	15.10
	2:2		(1 set)			
B&W mode	1:1	19.11	12.55	23.99	23.20	29.40
			7.42	11.96	4 sets	
	1:2	32.28				15.08
	2:2					

Notes
Reports located: <http://www.hp.com/go/printerclaims>