

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Canon imageRUNNER ADVANCE C350iF

Printing device and settings		
Test Start Date and Time	9/17/2014 6:50	
Tester	KN	
Machine name/model	Canon imageRUNNER ADVANCE C350iF	
Colour or B&W	Colour	
FW Version	FEQ14481	
Temperature and Humidity	78 degF / 26 degC, 37 %rH	
Voltage	110V	
Test End Date and Time	6/18/2015 4:50	

Item	Value	
Mode and Setting	Driver Version	Canon iR-ADV C250/350 UFR II
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black and White
	Duplex B&W Settings	Black and White
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
	Office Category Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	15.5	36.0
	Duplex	19.9	36.9
B&W	Simplex	13.6	37.3
	Duplex	18.0	36.4

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
			1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	
Color Mode	Simplex - Adobe Reader	15.93	15.06 (1 set)	31.26 (9 sets)	31.16 (43 sets)	36.19
	Simplex - Word	15.20	15.78 (1 set)	31.28 (9 sets)		37.42
	Simplex - Excel	15.16	15.82 (1 set)	30.05 (8 sets)		34.65
	Simplex - Average	15.5	15.5	30.8	31.1	36.0
	Duplex - Adobe Reader	20.30	11.80 (1 set)	29.44 (8 sets)		37.42
	Duplex - Word	19.70	12.16 (1 set)	28.98 (8 sets)		36.04
	Duplex - Excel	19.62	12.22 (1 set)	29.32 (8 sets)		37.42
	Duplex - Average	19.9	12.0	29.2		36.9
B&W mode (optional for color device)	Simplex - Adobe Reader	13.82	17.35 (1 set)	32.61 (8 sets)	33.57 (43 sets)	37.34
	Simplex - Word	13.27	18.08 (1 set)	32.93 (8 sets)		37.34
	Simplex - Excel	13.45	17.83 (1 set)	32.83 (8 sets)		37.33
	Simplex - Average	13.6	17.7	32.7	33.5	37.3
	Duplex - Adobe Reader	18.03	13.30 (1 set)	29.80 (8 sets)		37.38
	Duplex - Word	18.22	13.18 (1 set)	30.42 (8 sets)		37.38
	Duplex - Excel	17.64	13.60 (1 set)	28.28 (8 sets)		34.44
	Duplex - Average	18.0	13.3	29.5		36.4

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/100
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Canon imageRUNNER ADVANCE C350iF

Printing device and settings		
Test Start Date and Time	9/17/2014 6:50	
Tester	KN	
Machine name/model	Canon imageRUNNER ADVANCE C350iF	
Colour or B&W	Colour	
FW Version	FEQ14481	
Temperature and Humidity	78 degF / 26 degC, 37 %rH	
Voltage	110V	
Test End Date and Time	6/18/2015 4:50	

Item	Value	
Mode and Setting	Driver Version	Canon IR-ADV C250/350 UFR II
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black and White
	Duplex B&W Settings	Black and White
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	16.0	34.9
	Duplex	20.5	34.9
B&W	Simplex	13.9	35.3
	Duplex	18.6	35.3

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4						
	Office Category Test	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Colour Mode	Simplex - Adobe Reader	16.33	14.69 (1 set)	30.06 (8 sets)	27.70 (41 sets)	35.38
	Simplex - Word	15.67	15.31 (1 set)	30.39 (8 sets)		35.38
	Simplex - Excel	15.74	15.23 (1 set)	29.54 (8 sets)		34.14
	Simplex - Average	16.0	15.0	29.9	27.7	34.9
	Duplex - Adobe Reader	20.83	11.52 (1 set)	28.06 (8 sets)		35.38
	Duplex - Word	20.33	11.80 (1 set)	26.94 (8 sets)		34.14
	Duplex - Excel	20.23	11.86 (1 set)	28.34 (8 sets)		35.38
	Duplex - Average	20.5	11.7	27.7		34.9
B&W mode (optional for color device)	Simplex - Adobe Reader	14.21	16.88 (1 set)	31.06 (8 sets)	32.24 (41 sets)	35.34
	Simplex - Word	13.69	17.52 (1 set)	31.35 (8 sets)		35.34
	Simplex - Excel	13.73	17.47 (1 set)	31.28 (8 sets)		35.34
	Simplex - Average	13.9	17.2	31.2	32.2	35.3
	Duplex - Adobe Reader	18.67	12.84 (1 set)	28.70 (8 sets)		35.36
	Duplex - Word	18.89	12.70 (1 set)	29.22 (8 sets)		35.36
	Duplex - Excel	18.21	13.16 (1 set)	28.08 (8 sets)		35.36
	Duplex - Average	18.6	12.9	28.6		35.3

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER

Canon imageRUNNER ADVANCE C350iF

Printing device and settings	
Test Start Date and Time	9/17/2014 6:50
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 24 degC, 44 %rH
Voltage	110V
Test End Date and Time	8/6/2015 10:42

Item	Value
Mode and Setting	
PDL and driver version	Canon iR-ADV C250/350 UFR II
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: Letter		
		FPOt from Ready (seconds)
Color	Simplex	10.46
	Duplex	16.30
B&W	Simplex	8.48
	Duplex	14.62

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category						
Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOt from Ready - Simplex	10.17	10.39	10.82	10.46	48 Seconds
	FPOt from Ready - Duplex	15.97	16.18	16.73	16.3	48 Seconds
	FPOt from Sleep - Simplex			23.90		300 Minutes
	Recovery Time			13.1		
	FPOt from Off - Simplex			76.36		
	Warm-up Time			65.54		
B&W Mode	FPOt from Ready - Simplex	8.20	8.51	8.72	8.48	48 Seconds
	FPOt from Ready - Duplex	14.36	14.51	14.97	14.62	48 Seconds
	FPOt from Sleep - Simplex			23.64		300 Minutes
	Recovery Time			14.9		
	FPOt from Off - Simplex			31.52		
	Warm-up Time			22.80		

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection	TCP/IP	10/1000
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4 Canon iR-ADV C250/350 UFR II

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Canon imageRUNNER ADVANCE C350iF

Printing device and settings	
Test Start Date and Time	9/17/2014 6:50
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 24 degC, 44 %rH
Voltage	110V
Test End Date and Time	8/6/2015 10:42

Item	Value
Mode and Setting	
PDL and driver version	Canon iR-ADV C250/350 UFR II
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		
		F POT from Ready (seconds)
Colour	Simplex	10.58
	Duplex	16.66
B&W	Simplex	8.64
	Duplex	15.06

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category						
Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Colour Mode	F POT from Ready - Simplex	10.29	10.51	10.94	10.58	48 Seconds
	F POT from Ready - Duplex	16.21	16.36	17.39	16.66	48 Seconds
	F POT from Sleep - Simplex			24.12		300 Minutes
	Recovery Time			13.2		
	F POT from Off - Simplex			26.01		
	Warm-up Time			15.07		
B&W Mode	F POT from Ready - Simplex	8.42	8.60	8.90	8.64	48 Seconds
	F POT from Ready - Duplex	14.59	15.48	15.10	15.06	48 Seconds
	F POT from Sleep - Simplex			23.35		300 Minutes
	Recovery Time			14.5		
	F POT from Off - Simplex			22.24		
	Warm-up Time			13.34		

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection	TCP/IP	10/1000
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4 Canon iR-ADV C250/350 UFR II

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER

Canon imageRUNNER ADVANCE C350iF

Machine Setup Information	
Test Start Date and Time	9/17/2014 8:55
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC, 39 %rH
Test End Date and Time	8/13/2015 14:19

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	7.5	37.4
B&W	5.9	37.3

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	7.00	8.57	30.59 24 sets	32.35 164 sets	37.42
	B	7.40	8.11	30.66 24 sets		37.43
	C	7.85	7.63	30.70 24 sets		37.42
	D	7.56	7.94	30.32 24 sets		37.42
	Average	7.5	8.0	30.5	32.3	37.4
B&W	A	5.52	10.86	31.50 24 sets	33.93 165 sets	37.36
	B	5.87	10.22	31.52 24 sets		37.35
	C	6.27	9.56	31.68 24 sets		37.38
	D	5.81	10.32	31.68 24 sets		37.35
	Average	5.9	10.2	31.5	33.9	37.3

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Canon imageRUNNER ADVANCE C350iF

Machine Setup Information	
Test Start Date and Time	9/17/2014 8:55
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 24 degC, 39 %rH
Test End Date and Time:	8/13/2015 14:19

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	7.4	35.3
B&W	6.1	35.3

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	7.43	8.08	29.01 23 sets	30.54 156 sets	35.40
	B	7.90	7.60	29.00 23 sets		35.40
	C	7.07	8.48	29.01 23 sets		35.40
	D	7.05	8.50	29.03 23 sets		35.39
	Average	7.4	8.1	29.0	30.5	35.3
B&W	A	5.77	10.41	29.67 22 sets	31.72 154 sets	35.35
	B	6.35	9.45	29.91 23 sets		35.37
	C	5.65	10.62	30.20 23 sets		35.35
	D	6.43	9.33	30.13 23 sets		35.36
	Average	6.1	9.9	29.9	31.7	35.3

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	10/8/2014 11:58
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 25 degC, 29 %rH
Test End Date and Time	10/9/2014 13:20
Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	
Color Mode	1:1	14.75	16.26	32.22	31.42	37.42
			(1 set)	8 sets	43 sets	
	1:2	19.56	12.26	29.80		37.42
			(1 set)	8 sets		
	2:2	25.70	9.32	26.52		37.42
			(1 set)	8 sets		
B&W mode	1:1	13.32	18.01	32.89	33.92	37.35
				8 sets	43 sets	
	1:2	18.50	12.96	30.20		37.40
				8 sets		
	2:2	24.60	9.74	26.86		35.84
				8 sets		

Notes
Reports located: <http://www.hp.com/go/printerclaims>

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	10/8/2014 11:58
Tester	KN
Machine name/model	Canon imageRUNNER ADVANCE C350iF
Colour or B&W	Colour
FW Version	FEQ14481
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 25 degC, 29 %rH
Test End Date and Time	10/9/2014 13:20

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	15.30	15.68	29.81	29.42	34.15
			(1 set)	8 sets	41 sets	
	1:2	20.88	11.48	28.32	8 sets	35.38
B&W mode	2:2	26.52	9.02	25.90	8 sets	35.38
			(1 set)	8 sets	8 sets	
	1:1	13.77	17.42	31.38	31.84	35.34
B&W mode	1:2	18.97	12.64	28.92	8 sets	35.16
			9.52	25.78	8 sets	
	2:2	25.14	9.52	25.78	8 sets	35.36

Notes
 Reports located: <http://www.hp.com/go/printerclaims>