

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Dell C3765dnf Color MFP

Printing device and settings		
Test Start Date and Time	6/16/2015 15:48	
Tester	AH	
Machine name/model	C3765dnf Color MFP	
Colour or B&W	Colour	
FW Version	20130424	
Temperature and Humidity	75 degF / 24 degC, 35 %rH	
Voltage	110V	
Test End Date and Time	6/23/2015 18:32	

Item	Value	
Mode and Setting	Driver Version	61.145.2.15674
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Grayscale
	Duplex B&W Settings	Grayscale
	Setting N set count	Application
Paper Path	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
Paper	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
		FSOT (seconds)	ESAT (ipm)
Color	Office Category Test for Color Device		
	Simplex	14.7	36.7
B&W	Duplex	18.1	24.2
	Simplex	13.9	36.7
	Duplex	17.5	24.2

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	14.93	16.05 (1 set)	30.02 (6 sets)	32.00 (41 sets)	36.79
	Simplex - Word	14.59	16.43 (1 set)	30.50 (6 sets)		36.79
	Simplex - Excel	14.56	16.47 (1 set)	30.47 (6 sets)		36.81
	Simplex - Average	14.7	16.3	30.3	32.0	36.7
	Duplex - Adobe Reader	18.26	13.12 (1 set)	20.70 (5 sets)		24.28
	Duplex - Word	17.91	13.38 (1 set)	20.88 (5 sets)		24.28
	Duplex - Excel	17.89	13.40 (1 set)	20.86 (5 sets)		24.26
	Duplex - Average	18.1	13.3	20.8		24.2
B&W mode <small>(optional for color device)</small>	Simplex - Adobe Reader	14.22	16.87 (1 set)	30.56 (6 sets)	31.69 (41 sets)	36.81
	Simplex - Word	13.68	17.53 (1 set)	31.09 (6 sets)		36.77
	Simplex - Excel	13.70	17.50 (1 set)	30.95 (6 sets)		36.79
	Simplex - Average	13.9	17.3	30.8	31.6	36.7
	Duplex - Adobe Reader	18.28	13.12 (1 set)	20.60 (5 sets)		24.28
	Duplex - Word	17.05	14.06 (1 set)	21.24 (5 sets)		24.30
	Duplex - Excel	17.05	14.06 (1 set)	21.18 (5 sets)		24.30
	Duplex - Average	17.5	13.7	21.0		24.2

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 - 3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family, SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCASHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Dell C3765dnf Color MFP

Printing device and settings		
Test Start Date and Time	6/16/2015 15:48	
Tester	AH	
Machine name/model	C3765dnf Color MFP	
Colour or B&W	Colour	
FW Version	20130424	
Temperature and Humidity	75 degF / 24 degC, 35 %rH	
Voltage	110V	
Test End Date and Time	6/23/2015 18:32	

Item	Value	
Mode and Setting	Driver Version	61.145.2.15674
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Grayscale
	Duplex B&W Settings	Grayscale
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	15.1	35.0
	Duplex	18.5	23.5
B&W	Simplex	14.3	35.0
	Duplex	17.9	23.4

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Colour Mode	Simplex - Adobe Reader	15.25	15.73 (1 set)	28.88 (6 sets)	29.60 (39 sets)	35.04
	Simplex - Word	14.86	16.14 (1 set)	29.29 (6 sets)		35.07
	Simplex - Excel	14.90	16.09 (1 set)	29.24 (6 sets)		35.04
	Simplex - Average	15.1	15.9	29.1	29.6	35.0
	Duplex - Adobe Reader	18.55	12.92 (1 set)	20.16 (5 sets)		23.48
	Duplex - Word	18.23	13.14 (1 set)	20.30 (5 sets)		23.50
	Duplex - Excel	18.67	12.84 (1 set)	20.28 (5 sets)		23.52
	Duplex - Average	18.5	12.9	20.2		23.5
B&W mode (optional for color device)	Simplex - Adobe Reader	14.56	16.48 (1 set)	29.47 (6 sets)	30.14 (39 sets)	35.04
	Simplex - Word	14.10	17.00 (1 set)	29.79 (6 sets)		35.04
	Simplex - Excel	14.15	16.95 (1 set)	29.78 (6 sets)		35.04
	Simplex - Average	14.3	16.8	29.6	30.1	35.0
	Duplex - Adobe Reader	18.80	12.76 (1 set)	20.05 (5 sets)		23.50
	Duplex - Word	17.32	13.84 (1 set)	20.60 (5 sets)		23.50
	Duplex - Excel	17.45	13.74 (1 set)	20.56 (5 sets)		23.48
	Duplex - Average	17.9	13.4	20.4		23.4

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aC5HR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER

Dell C3765dnf Color MFP

Printing device and settings	
Test Start Date and Time	6/15/2015 18:06
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Default
Controller	5
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	74 degF / 24 degC, 32 %rH
Voltage	110V
Test End Date and Time	6/25/2015 16:44

Item	Value	
Mode and Setting	PDL and driver version	61.145.2.15674
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
Paper	Paper type setting	default
	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: Letter		
FPOT from Ready (seconds)		
Color	Simplex	9.48
	Duplex	12.87
B&W	Simplex	8.67
	Duplex	12.86

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex	9.34	9.44	9.66	9.48	49 Seconds
	FPOT from Ready - Duplex	12.70	12.81	13.08	12.87	49 Seconds
	FPOT from Sleep - Simplex			23.43		63 Minutes
	Recovery Time			13.8		
	FPOT from Off - Simplex			47.55		
	Warm-up Time			37.89		
B&W Mode	FPOT from Ready - Simplex	8.44	8.64	8.92	8.67	49 Seconds
	FPOT from Ready - Duplex	11.85	13.15	13.56	12.86	49 Seconds
	FPOT from Sleep - Simplex			22.28		63 Minutes
	Recovery Time			13.4		
	FPOT from Off - Simplex			48.32		
	Warm-up Time			39.40		

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection	TCP/IP	10/1000
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4 61.145.2.15674

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Dell C3765dnf Color MFP

Printing device and settings	
Test Start Date and Time	6/15/2015 18:06
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Default
Controller	5
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	74 degF / 24 degC, 32 %rH
Voltage	110V
Test End Date and Time	6/25/2015 16:44

Item	Value
Mode and Setting	
PDL and driver version	61.145.2.15674
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
Paper	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
Paper Path	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		
		FPOt from Ready (seconds)
Colour	Simplex	9.55
	Duplex	13.05
B&W	Simplex	8.76
	Duplex	12.53

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Post monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Colour Mode	FPOt from Ready - Simplex	9.38	9.53	9.71	9.55	49 Seconds
	FPOt from Ready - Duplex	12.83	12.98	13.32	13.05	49 Seconds
	FPOt from Sleep - Simplex			23.05		63 Minutes
	Recovery Time			13.3		
	FPOt from Off - Simplex			49.64		
	Warm-up Time			39.93		
B&W Mode	FPOt from Ready - Simplex	8.53	8.69	9.03	8.76	49 Seconds
	FPOt from Ready - Duplex	12.13	12.12	13.31	12.53	49 Seconds
	FPOt from Sleep - Simplex			23.49		63 Minutes
	Recovery Time			14.5		
	FPOt from Off - Simplex			46.16		
	Warm-up Time			37.11		

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Post monitor not configured to follow device if the IP address changes.
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
Test System	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection		
TCP/IP	10/1000	
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4 61.145.2.15674

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER

Dell C3765dnf Color MFP

Machine Setup Information

Test Start Date and Time	8/3/2012 11:45
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Not Specified
Temperature and Humidity	79 degF / 26 degC, 31 %rH
Test End Date and Time	6/29/2015 16:43

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
	Paper Feeding	Tray 2
Paper Path	Paper Exit	Default
	Face Up Exit	Default (face down)
	Fixing Capability	Default
Temporary Stop	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	14.3	36.7
B&W	11.4	36.8

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the control panel, which prevents the 4 minute test from reaching 4 minutes.

Detailed Report: LETTER

	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	14.88	4.03	27.74 24 sets	31.00 99 sets	36.81
	B	13.57	4.41	27.76 24 sets		36.79
	C	14.35	4.17	27.78 24 sets		36.83
	D	14.37	4.17	27.27 21 sets		36.76
	Average	14.3	4.1	27.6	31.0	36.7
	B&W	A	12.47	4.80	29.65 24 sets	31.25 99 sets
B		11.00	5.44	29.67 24 sets		36.81
C		11.06	5.42	29.65 24 sets		36.81
D		10.95	5.47	29.72 24 sets		36.79
Average		11.4	5.2	29.6	31.2	36.8

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the control panel, which prevents the 4 minute test from reaching 4 minutes.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Dell C3765dnf Color MFP

Machine Setup Information

Test Start Date and Time	8/3/2012 11:45
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Not Specified
Temperature and Humidity	79 degF / 26 degC, 31 %rH
Test End Date and Time	6/29/2015 16:43

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
	Paper Feeding	Tray 2
Paper Path	Paper Exit	Default
	Face Up Exit	Default (face down)
	Fixing Capability	Default
Temporary Stop	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	14.1	35.0
B&W	11.1	35.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the control panel, which prevents the 4 minute test from reaching 4 minutes.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	14.47	4.13	26.74 23 sets	26.22 99 sets	35.04
	B	13.93	4.30	26.70 23 sets		35.06
	C	13.96	4.29	26.73 23 sets		35.04
	D	13.95	4.29	26.67 23 sets		35.04
	Average	14.1	4.2	26.7	26.2	35.0
B&W	A	11.34	5.29	28.36 23 sets	30.27 99 sets	35.04
	B	10.97	5.46	28.35 23 sets		35.04
	C	10.98	5.46	27.18 23 sets		35.04
	D	10.98	5.46	28.35 23 sets		35.01
	Average	11.1	5.4	28.0	30.2	35.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the control panel, which prevents the 4 minute test from reaching 4 minutes.

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	7/31/2012 18:23
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Not Specified
Temperature and Humidity	85 degF / 29 degC, 28 %rH
Test End Date and Time:	6/29/2015 11:33
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (application)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard ext tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	27.37	8.76	23.57	29.28	35.21
			(1 set)	6 sets	34 sets	
	1:2	31.15	7.68	16.98		24.28
(1 set)			5 sets			
2:2	40.11	5.96	12.98		21.34	
		(1 set)	4 sets			
B&W mode	1:1	18.73	12.80	27.61	30.31	35.65
				6 sets	35 sets	
	1:2	25.76	9.30	18.80		24.30
			5 sets			
2:2	31.82	7.52	14.70		21.48	
			4 sets			

Notes
Reports located: <http://www.hp.com/go/printerclaims>

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	7/31/2012 18:23
Tester	AH
Machine name/model	C3765dnf Color MFP
Colour or B&W	Colour
FW Version	20130424
Configuration (options)	Not Specified
Temperature and Humidity	85 degF / 29 degC, 28 %rH
Test End Date and Time:	6/29/2015 11:33
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (application)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard ext tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	27.15	8.83	22.80	27.25	33.46
			(1 set)	6 sets	32 sets	
	1:2	31.26	7.66	16.64		23.52
(1 set)			5 sets			
2:2	40.63	5.90	12.74		20.82	
		(1 set)	4 sets			
B&W mode	1:1	19.11	12.55	26.56	29.05	34.09
				6 sets	34 sets	
	1:2	24.83	9.66	18.52		23.52
			5 sets			
2:2	32.29	7.42	14.40		20.92	
			4 sets			

Notes
Reports located: <http://www.hp.com/go/printerclaims>