

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Kyocera ECOSYS M6526cidn

Printing device and settings		
Test Start Date and Time	4/22/2014 16:34	
Tester	KN	
Machine name/model	Kyocera ECOSYS M6526cidn	
Colour or B&W	Colour	
FW Version	Unknown	
Temperature and Humidity	74 degF / 23 degC, 35 %rH	
Voltage	110V	
Test End Date and Time	6/17/2015 15:43	

Item	Value	
Mode and Setting	Driver Version	Unknown
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black
	Duplex B&W Settings	Black
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
Office Category	Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	20.7	26.6
	Duplex	29.1	13.8
B&W	Simplex	17.4	26.9
	Duplex	27.9	13.9

- Notes
- 1) All printing device and driver settings were default mode.
  - 2) For the B/W results, the print driver was set to "print in B/W".
  - 3) For more information see <http://www.hp.com/go/printerclaims>.
  - 4) Port monitor not configured to follow device if the IP address changes.
  - 5) Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Detailed Report: LETTER

	Office Category	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	
Color Mode	Simplex - Adobe Reader	22.67	10.58 ( 1 set )	20.08 ( 7 sets )	25.75 ( 33 sets )	27.16
	Simplex - Word	21.96	10.92 ( 1 set )	19.90 ( 7 sets )		26.36
	Simplex - Excel	17.30	13.86 ( 1 set )	20.14 ( 7 sets )		26.49
	Simplex - Average	20.7	11.7	20.0	25.7	26.6
	Duplex - Adobe Reader	29.28	8.18 ( 1 set )	11.72 ( 5 sets )		13.82
	Duplex - Word	29.47	8.12 ( 1 set )	11.68 ( 5 sets )		13.76
	Duplex - Excel	28.42	8.42 ( 1 set )	11.88 ( 5 sets )		13.84
	Duplex - Average	29.1	8.2	11.7		13.8
B&W mode (optional for color device)	Simplex - Adobe Reader	17.26	13.90 ( 1 set )	21.93 ( 5 sets )	19.91 ( 31 sets )	26.56
	Simplex - Word	16.95	14.16 ( 1 set )	22.24 ( 5 sets )		26.65
	Simplex - Excel	17.85	13.44 ( 1 set )	22.44 ( 5 sets )		27.68
	Simplex - Average	17.4	13.8	22.2	19.9	26.9
	Duplex - Adobe Reader	27.98	8.56 ( 1 set )	11.18 ( 3 sets )		13.94
	Duplex - Word	27.36	8.76 ( 1 set )	11.30 ( 3 sets )		13.86
	Duplex - Excel	28.13	8.52 ( 1 set )	11.18 ( 3 sets )		13.94
	Duplex - Average	27.9	8.6	11.2		13.9

- Notes
- 1) All printing device and driver settings were default mode.
  - 2) For the B/W results, the print driver was set to "print in B/W".
  - 3) For more information see <http://www.hp.com/go/printerclaims>.
  - 4) Port monitor not configured to follow device if the IP address changes.
  - 5) Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aC5HR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Kyocera ECOSYS M6526cidn

Printing device and settings		
Test Start Date and Time	4/22/2014 16:34	
Tester	KN	
Machine name/model	Kyocera ECOSYS M6526cidn	
Colour or B&W	Colour	
FW Version	Unknown	
Temperature and Humidity	74 degF / 23 degC, 35 %rH	
Voltage	110V	
Test End Date and Time	6/17/2015 15:43	

Item	Value	
Mode and Setting	Driver Version	Unknown
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Black
	Duplex B&W Settings	Black
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4

Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Colour	Simplex	22.8	25.3
	Duplex	34.1	13.4
B&W	Simplex	18.0	26.0
	Duplex	28.6	13.5

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.
- 5) Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Detailed Report: A4

	Office Category Test	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Colour Mode	Simplex - Adobe Reader	23.95	10.01 ( 1 set )	17.51 ( 5 sets )	23.76 ( 30 sets )	25.83
	Simplex - Word	20.50	11.70 ( 1 set )	18.40 ( 5 sets )		25.05
	Simplex - Excel	23.83	10.07 ( 1 set )	17.35 ( 5 sets )		25.04
	Simplex - Average	22.8	10.5	17.7	23.7	25.3
	Duplex - Adobe Reader	35.06	6.82 ( 1 set )	9.44 ( 3 sets )		13.46
	Duplex - Word	31.84	7.52 ( 1 set )	10.02 ( 3 sets )		13.44
	Duplex - Excel	35.11	6.82 ( 1 set )	9.52 ( 3 sets )		13.48
	Duplex - Average	34.1	7.0	9.6		13.4
B&W mode <small>(optional for color device)</small>	Simplex - Adobe Reader	17.81	13.47 ( 1 set )	21.64 ( 5 sets )	25.13 ( 29 sets )	26.41
	Simplex - Word	17.40	13.79 ( 1 set )	21.30 ( 5 sets )		25.36
	Simplex - Excel	18.58	12.91 ( 1 set )	20.86 ( 5 sets )		26.35
	Simplex - Average	18.0	13.3	21.2	25.1	26.0
	Duplex - Adobe Reader	28.57	8.38 ( 1 set )	10.92 ( 3 sets )		13.60
	Duplex - Word	27.91	8.58 ( 1 set )	11.00 ( 3 sets )		13.50
	Duplex - Excel	29.07	8.24 ( 1 set )	10.88 ( 3 sets )		13.60
	Duplex - Average	28.6	8.4	10.9		13.5

Notes

- 1) All printing device and driver settings were default mode.
- 2) For the B/W results, the print driver was set to "print in B/W".
- 3) For more information see <http://www.hp.com/go/printerclaims>.
- 4) Port monitor not configured to follow device if the IP address changes.
- 5) Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Test System Parameters

Item	Value
Computer	HP Compag Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCASHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

**ISO/IEC 17629 First Print Out Time Report: Office Category**

Full Detailed Test Report - LETTER

Kyocera ECOSYS M6526cidn

Printing device and settings	
Test Start Date and Time	4/17/2014 18:47
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC, 20 %rH
Voltage	110V
Test End Date and Time	6/12/2015 14:16

Item	Value	
<b>Mode and Setting</b>	PDL and driver version	Unknown
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
<b>Paper</b>	Paper type setting	default
	Paper feeding	Standard cassette
<b>Paper Path</b>	Paper exit	Standard exit tray
	Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category		
Summary Report: LETTER		
		F POT from Ready (seconds)
<b>Color</b>	Simplex	10.59
	Duplex	12.06
<b>B&amp;W</b>	Simplex	9.74
	Duplex	19.23
Notes		
1) All printing device and driver settings were default mode.		
2) For the B/W results, the print driver was set to "print in B/W".		
3) For more information see <a href="http://www.hp.com/go/printerclaims">http://www.hp.com/go/printerclaims</a> .		
4) Port monitor not configured to follow device if the IP address changes.		
5) Page counts were collected after completion of the tests.		

ISO First Page Out Time Report: Office Category						
Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Color Mode</b>	F POT from Ready - Simplex	10.20	10.27	11.29	10.59	21 Seconds
	F POT from Ready - Duplex	11.84	11.97	12.34	12.06	21 Seconds
	F POT from Sleep - Simplex			31.93		75 Minutes
	Recovery Time			20.6		
	F POT from Off - Simplex			0.00		
	Warm-up Time			-11.29		
<b>B&amp;W Mode</b>	F POT from Ready - Simplex	9.49	9.64	10.08	9.74	21 Seconds
	F POT from Ready - Duplex	18.96	18.78	19.94	19.23	21 Seconds
	F POT from Sleep - Simplex			25.96		75 Minutes
	Recovery Time			15.9		
	F POT from Off - Simplex			0.00		
	Warm-up Time			-10.08		
Notes						
1) All printing device and driver settings were default mode.						
2) For the B/W results, the print driver was set to "print in B/W".						
3) For more information see <a href="http://www.hp.com/go/printerclaims">http://www.hp.com/go/printerclaims</a> .						
4) Port monitor not configured to follow device if the IP address changes.						
5) Page counts were collected after completion of the tests.						

Test System Parameters		
Item	Value	
<b>Test System</b>	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aCSHR ATA
	I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0	
<b>Printing Device Connection</b>	TCP/IP	10/1000
<b>Software</b>	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Printing Applications	Adobe Reader 10.1.4
	Print Driver	Unknown

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4

Kyocera ECOSYS M6526cidn

Printing device and settings	
Test Start Date and Time	4/17/2014 18:47
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Default
Controller	Unknown
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC, 20 %rH
Voltage	110V
Test End Date and Time	6/12/2015 14:16

Item	Value
<b>Mode and Setting</b>	
PDL and driver version	Unknown
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
<b>Paper</b>	
Paper type setting	default
Paper feeding	Standard cassette
Paper exit	Standard exit tray
<b>Paper Path</b>	
Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		
		FPO from Ready (seconds)
<b>Colour</b>	Simplex	10.75
	Duplex	19.36
<b>B&amp;W</b>	Simplex	9.91
	Duplex	18.04

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Colour Mode</b>	FPO from Ready - Simplex	10.15	10.66	11.42	10.75	21 Seconds
	FPO from Ready - Duplex	18.96	19.13	19.99	19.36	21 Seconds
	FPO from Sleep - Simplex			0.00		75 Minutes
	Recovery Time			0.0		
	FPO from Off - Simplex			0.00		
	Warm-up Time			-11.42		
<b>B&amp;W Mode</b>	FPO from Ready - Simplex	9.51	10.08	10.14	9.91	21 Seconds
	FPO from Ready - Duplex	17.68	18.07	18.36	18.04	21 Seconds
	FPO from Sleep - Simplex			25.95		75 Minutes
	Recovery Time			15.8		
	FPO from Off - Simplex			0.00		
	Warm-up Time			-10.14		

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.  
 5) Page counts were collected after completion of the tests.

Test System Parameters		
Item	Value	
<b>Test System</b>	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aC5HR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
<b>Printing Device Connection</b>		
TCP/IP	10/1000	
<b>Software</b>	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4

**ISO/IEC 29183 Copy Productivity Report**

Full Detailed Test Report - LETTER

Kyocera ECOSYS M6526cidn

Machine Setup Information	
Test Start Date and Time	5/29/2014 14:12
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 23 %rH
Test End Date and Time	6/3/2014 12:13

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	9.2	27.3
B&W	9.3	27.7

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	9.17	6.53	22.88 16 sets	26.33 120 sets	27.46
	B	9.15	6.55	22.67 16 sets		27.13
	C	9.15	6.56	23.04 17 sets		27.36
	D	9.14	6.56	23.19 17 sets		27.60
	Average	9.2	6.5	22.9	26.3	27.3
B&W	A	9.17	6.54	23.16 17 sets	26.68 122 sets	27.69
	B	9.29	6.45	22.94 16 sets		27.65
	C	9.29	6.45	22.97 16 sets		27.73
	D	9.26	6.47	23.00 16 sets		27.78
	Average	9.3	6.4	23.0	26.6	27.7

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

**ISO/IEC 29183 Copy Productivity Report**

Full Detailed Test Report - A4

Kyocera ECOSYS M6526cidn

Machine Setup Information	
Test Start Date and Time	5/29/2014 14:12
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 23 %rH
Test End Date and Time:	6/3/2014 12:13

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	9.3	26.0
B&W	9.4	26.2

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	9.23	6.50	21.97 16 sets	25.35 114 sets	26.20
	B	9.25	6.48	21.62 15 sets		26.01
	C	9.27	6.46	21.85 16 sets		26.01
	D	9.23	6.49	21.95 16 sets		26.15
	Average	9.3	6.4	21.8	25.3	26.0
B&W	A	9.40	6.37	21.79 15 sets	24.99 106 sets	26.34
	B	9.30	6.44	22.01 16 sets		26.33
	C	9.39	6.38	21.78 15 sets		25.99
	D	9.42	6.36	22.10 16 sets		26.44
	Average	9.4	6.3	21.9	24.9	26.2

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	6/16/2014 14:27
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Not Specified
Temperature and Humidity	77 degF / 25 degC, 32 %rH
Test End Date and Time	6/16/2014 17:57

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	16.94	14.17	22.27	25.98	26.63
			( 1 set )	5 sets	28 sets	
	1:2	29.20	8.20	11.06	⌘	13.82
			( 1 set )	3 sets	⌘	
	2:2	29.93	8.00	10.84	⌘	13.74
			( 1 set )	3 sets	⌘	
B&W mode	1:1	15.95	15.04	23.30	26.52	27.27
				5 sets	29 sets	
	1:2	28.82	8.32	11.22	⌘	13.94
				3 sets	⌘	
	2:2	29.45	8.14	10.98	⌘	13.90
				3 sets	⌘	

Notes  
 Reports located: <http://www.hp.com/go/printerclaims>  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	6/16/2014 14:27
Tester	KN
Machine name/model	Kyocera ECOSYS M6526cidn
Colour or B&W	Colour
FW Version	Unknown
Configuration (options)	Not Specified
Temperature and Humidity	77 degF / 25 degC, 32 %rH
Test End Date and Time	6/16/2014 17:57

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default

Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	16.81	14.27	21.85	24.75	25.52
			( 1 set )	5 sets	27 sets	
	1:2	29.79	8.04	10.84	3 sets	13.46
B&W mode	1:1	16.56	14.48	21.90	25.20	26.06
			( 1 set )	3 sets	27 sets	
	1:2	29.32	8.18	10.92	3 sets	13.54
B&W mode	2:2	30.07	7.98	10.74	3 sets	13.56
			( 1 set )	3 sets	3 sets	

Notes  
 Reports located: <http://www.hp.com/go/printerclaims>  
 Note: Only 1 iteration was completed for the 4 minute test because of frequent paper jams.