

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Samsung ProXpress C2670FW

Printing device and settings		
Test Start Date and Time	6/9/2015 22:45	
Tester	KN	
Machine name/model	ProXpress C2670FW	
Colour or B&W	Colour	
FW Version	V4.00.01.02 JUN-01-2014	
Temperature and Humidity	32 degF / 0 degC, 0 %RH	
Voltage	110V	
Test End Date and Time	6/22/2015 3:53	

	Item	Value
Mode and Setting	Driver Version	v5.2.3790.1830
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	
	Duplex B&W Settings	Grayscale
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
Color	Simplex	22.6	23.2
	Duplex	31.8	13.5
B&W	Simplex	20.3	27.0
	Duplex	29.4	13.5

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
Color Mode	Simplex - Adobe Reader	23.12	10.37 ( 1 set )	16.46 ( 4 sets )	22.86 ( 28 sets )	21.18
	Simplex - Word	22.12	10.84 ( 1 set )	20.92 ( 5 sets )		27.02
	Simplex - Excel	22.50	10.66 ( 1 set )	16.94 ( 4 sets )		21.66
	Simplex - Average	22.6	10.6	18.1	22.8	23.2
	Duplex - Adobe Reader	32.57	7.36 ( 1 set )	10.14 ( 3 sets )		13.56
	Duplex - Word	31.50	7.60 ( 1 set )	10.58 ( 3 sets )		13.54
	Duplex - Excel	31.26	7.66 ( 1 set )	10.32 ( 3 sets )		13.56
	Duplex - Average	31.8	7.5	10.3		13.5
B&W mode (optional for color device)	Simplex - Adobe Reader	20.58	11.65 ( 1 set )	21.37 ( 5 sets )	24.00 ( 30 sets )	27.01
	Simplex - Word	19.93	12.04 ( 1 set )	21.68 ( 5 sets )		27.04
	Simplex - Excel	20.22	11.86 ( 1 set )	21.53 ( 5 sets )		27.02
	Simplex - Average	20.3	11.8	21.5	24.0	27.0
	Duplex - Adobe Reader	29.55	8.10 ( 1 set )	10.78 ( 3 sets )		13.56
	Duplex - Word	29.07	8.24 ( 1 set )	11.08 ( 3 sets )		13.56
	Duplex - Excel	29.48	8.11 ( 1 set )	10.86 ( 3 sets )		13.58
	Duplex - Average	29.4	8.1	10.9		13.5

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 - 3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family, SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

**ISO/IEC 24734 Printing Productivity Report: Office Category**

**Full Detailed Test Report - A4**

Samsung ProXpress C2670FW

Printing device and settings	
Test Start Date and Time	6/9/2015 22:45
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Temperature and Humidity	32 degF / 0 degC, 0 %RH
Voltage	110V
Test End Date and Time	6/22/2015 3:53

Item	Value	
<b>Mode and Setting</b>	Driver Version	v5.2.3790.1830
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	
	Duplex B&W Settings	Grayscale
	Setting N set count	Application
	Collating function	Activated (application)
<b>Paper Path</b>	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
<b>Paper</b>	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4			
Office Category Test for Color Device		FSOT (seconds)	ESAT (ipm)
<b>Colour</b>	Simplex	22.9	22.2
	Duplex	32.3	13.0
<b>B&amp;W</b>	Simplex	20.7	25.9
	Duplex	30.0	13.0

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec
<b>Colour Mode</b>	Simplex - Adobe Reader	23.54	10.19 ( 1 set )	15.48 ( 4 sets )	21.40 ( 25 sets )	19.69
	Simplex - Word	22.22	10.79 ( 1 set )	20.23 ( 5 sets )		25.96
	Simplex - Excel	22.69	10.57 ( 1 set )	16.48 ( 4 sets )		20.95
	Simplex - Average	22.9	10.5	17.3	21.4	22.2
	Duplex - Adobe Reader	33.08	7.24 ( 1 set )	9.76 ( 3 sets )		13.06
	Duplex - Word	32.06	7.48 ( 1 set )	10.28 ( 3 sets )		13.06
	Duplex - Excel	31.71	7.56 ( 1 set )	10.02 ( 3 sets )		13.04
	Duplex - Average	32.3	7.4	10.0		13.0
<b>B&amp;W mode</b> (optional for color device)	Simplex - Adobe Reader	20.88	11.48 ( 1 set )	20.43 ( 5 sets )	23.49 ( 29 sets )	25.96
	Simplex - Word	20.32	11.80 ( 1 set )	20.96 ( 5 sets )		25.96
	Simplex - Excel	20.62	11.63 ( 1 set )	20.84 ( 5 sets )		25.96
	Simplex - Average	20.7	11.6	20.7	23.4	25.9
	Duplex - Adobe Reader	30.26	7.92 ( 1 set )	10.48 ( 3 sets )		13.06
	Duplex - Word	29.53	8.11 ( 1 set )	10.74 ( 3 sets )		13.06
	Duplex - Excel	30.07	7.96 ( 1 set )	10.54 ( 3 sets )		13.06
	Duplex - Average	30.0	7.9	10.5		13.0

Notes  
 1) All printing device and driver settings were default mode.  
 2) For the B/W results, the print driver was set to "print in B/W".  
 3) For more information see <http://www.hp.com/go/printerclaims>.  
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

**ISO/IEC 17629 First Print Out Time Report: Office Category**

Full Detailed Test Report - LETTER

Samsung ProXpress C2670FW	
<b>Printing device and settings</b>	
Test Start Date and Time	6/5/2015 5:42
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Default
Controller	V0.01.22
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC, 39 %rH
Voltage	110V
Test End Date and Time	6/25/2015 13:29

	Item	Value
<b>Mode and Setting</b>	PDL and driver version	v5.2.3790.1830
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
<b>Paper</b>	Paper type setting	default
	Paper feeding	Standard cassette
<b>Paper Path</b>	Paper exit	Standard exit tray
	Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category		
Summary Report: <b>Letter</b>		
		<b>FPOT from Ready (seconds)</b>
<b>Color</b>	Simplex	15.13
	Duplex	22.58
<b>B&amp;W</b>	Simplex	12.87
	Duplex	20.01
Notes		
1) All printing device and driver settings were default mode.		
2) For the B/W results, the print driver was set to "print in B/W".		
3) For more information see <a href="http://www.hp.com/go/printerclaims">http://www.hp.com/go/printerclaims</a> .		
4) Port monitor not configured to follow device if the IP address changes.		
5) Page counts were collected after completion of the tests.		

ISO First Page Out Time Report: Office Category						
Detailed Report: <b>LETTER</b>						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Color Mode</b>	FPOT from Ready - Simplex	14.44	14.86	16.07	15.13	48 Seconds
	FPOT from Ready - Duplex	22.01	22.47	23.24	22.58	48 Seconds
	FPOT from Sleep - Simplex			18.52		65 Minutes
	Recovery Time			2.5		
	FPOT from Off - Simplex			85.28		
	Warm-up Time			69.21		
<b>B&amp;W Mode</b>	FPOT from Ready - Simplex	12.55	12.90	13.15	12.87	48 Seconds
	FPOT from Ready - Duplex	19.73	20.09	20.19	20.01	48 Seconds
	FPOT from Sleep - Simplex			15.90		65 Minutes
	Recovery Time			2.8		
	FPOT from Off - Simplex			93.87		
	Warm-up Time			80.72		
Notes						
1) All printing device and driver settings were default mode.						
2) For the B/W results, the print driver was set to "print in B/W".						
3) For more information see <a href="http://www.hp.com/go/printerclaims">http://www.hp.com/go/printerclaims</a> .						
4) Port monitor not configured to follow device if the IP address changes.						
5) Page counts were collected after completion of the tests.						

Test System Parameters		
Item	Value	
<b>Test System</b>	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aC SHR ATA
	I/O Subsystem	Builitn
	USB Subsystem	USB 2.0/3.0
<b>Printing Device Connection</b>	TCP/IP	10/1000
<b>Software</b>	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
	Print Driver	Adobe Reader 10.1.4
		v5.2.3790.1830

**ISO/IEC 17629 First Print Out Time Report: Office Category**

**Full Detailed Test Report - A4**

Samsung ProXpress C2670FW

Printing device and settings	
Test Start Date and Time	6/5/2015 5:42
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Default
Controller	V0.01.22
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	76 degF / 25 degC, 39 %rH
Voltage	110V
Test End Date and Time	6/25/2015 13:29

Item	Value
<b>Mode and Setting</b>	
PDL and driver version	v5.2.3790.1830
Print Quality mode	default
B&W settings	default
Paper feed orientation	Short Edge
<b>Paper</b>	
Paper type setting	default
Paper feeding	Standard cassette
<b>Paper Path</b>	
Paper exit	Standard exit tray
Output orientation	default (face up or face down)

**ISO First Page Out Time Summary Report: Office Category**

Summary Report: A4		
		F POT from Ready (seconds)
<b>Colour</b>	Simplex	15.05
	Duplex	22.81
<b>B&amp;W</b>	Simplex	13.09
	Duplex	20.35

- Notes
- 1) All printing device and driver settings were default mode.
  - 2) For the B/W results, the print driver was set to "print in B/W".
  - 3) For more information see <http://www.hp.com/go/printerclaims>.
  - 4) Port monitor not configured to follow device if the IP address changes.
  - 5) Page counts were collected after completion of the tests.

**ISO First Page Out Time Report: Office Category**

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
<b>Colour Mode</b>	F POT from Ready - Simplex	14.51	14.96	15.68	15.05	48 Seconds
	F POT from Ready - Duplex	22.33	22.69	23.39	22.81	48 Seconds
	F POT from Sleep - Simplex			17.72		65 Minutes
	Recovery Time			2.0		
	F POT from Off - Simplex			78.70		
	Warm-up Time			63.02		
<b>B&amp;W Mode</b>	F POT from Ready - Simplex	12.78	13.24	13.23	13.09	48 Seconds
	F POT from Ready - Duplex	19.97	20.53	20.53	20.35	48 Seconds
	F POT from Sleep - Simplex			15.72		65 Minutes
	Recovery Time			2.5		
	F POT from Off - Simplex			81.14		
	Warm-up Time			67.91		

- Notes
- 1) All printing device and driver settings were default mode.
  - 2) For the B/W results, the print driver was set to "print in B/W".
  - 3) For more information see <http://www.hp.com/go/printerclaims>.
  - 4) Port monitor not configured to follow device if the IP address changes.
  - 5) Page counts were collected after completion of the tests.

**Test System Parameters**

Item	Value
<b>Test System</b>	
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
<b>Printing Device Connection</b>	
TCP/IP	10/1000
<b>Software</b>	
Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
Printing Applications	Microsoft Office 2010 SP2
	Adobe Reader 10.1.4
Print Driver	v5.2.3790.1830

**ISO/IEC 29183 Copy Productivity Report**

Full Detailed Test Report - LETTER

Samsung ProXpress C2670FW

**Machine Setup Information**

Test Start Date and Time	12/2/2014 12:20
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Not Specified
Temperature and Humidity	77 degF / 25 degC, 21 %rH
Test End Date and Time	12/3/2014 11:57

	Pre-set Item	Pre-set Value
<b>Mode</b>	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
<b>Paper</b>	Paper Sending Direction	Default
	Paper Type Setting	Default
	Paper Feeding	Tray 2
<b>Paper Path</b>	Paper Exit	Default
	Face Up Exit	Default (face down)
	Fixing Capability	Default
<b>Temporary Stop</b>	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

<b>Paper</b>	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: **Letter**

	sFCOT	sESAT (ipm)
<b>Color</b>	13.9	23.0
<b>B&amp;W</b>	11.9	24.7

Notes  
First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: **LETTER**

	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
<b>Color</b>	A	13.90	4.30	16.89 17 sets	23.45 120 sets	23.19
	B	13.94	4.30	16.94 17 sets		23.19
	C	13.73	4.36	16.80 17 sets		22.98
	D	13.87	4.32	16.82 17 sets		22.97
	Average	13.9	4.3	16.8	23.4	23.0
<b>B&amp;W</b>	A	11.87	5.05	19.79 21 sets	24.68 131 sets	24.74
	B	11.80	5.08	19.71 21 sets		24.59
	C	11.71	5.11	20.03 22 sets		24.85
	D	11.87	5.05	20.04 22 sets		24.83
	Average	11.9	5.0	19.8	24.6	24.7

Notes  
First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

**ISO/IEC 29183 Copy Productivity Report**

**Full Detailed Test Report - A4**

Samsung ProXpress C2670FW

**Machine Setup Information**

Test Start Date and Time	12/2/2014 12:20
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Not Specified
Temperature and Humidity	77 degF / 25 degC, 21 %rH
Test End Date and Time	12/3/2014 11:57

	Pre-set Item	Pre-set Value
<b>Mode</b>	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
<b>Paper</b>	Paper Sending Direction	Default
	Paper Type Setting	Default
	Paper Feeding	Tray 2
<b>Paper Path</b>	Paper Exit	Default
	Face Up Exit	Default (face down)
	Fixing Capability	Default
<b>Temporary Stop</b>	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

<b>Paper</b>	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: <b>A4</b>		
	<b>sFCOT</b>	<b>sESAT (ipm)</b>
<b>Colour</b>	15.5	23.4
<b>B&amp;W</b>	12.0	23.8

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

Detailed Report: <b>A4</b>						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
<b>Colour</b>	A	14.04	4.26	18.57 20 sets	22.94 123 sets	25.26
	B	14.07	4.25	17.36 20 sets		22.90
	C	14.04	4.26	17.35 20 sets		22.89
	D	19.52	3.06	17.36 20 sets		22.90
	Average	15.5	3.9	17.6	22.9	23.4
<b>B&amp;W</b>	A	12.00	4.99	19.16 21 sets	23.01 131 sets	23.85
	B	11.98	5.00	19.14 21 sets		23.80
	C	11.90	5.03	19.37 22 sets		23.90
	D	11.95	5.01	19.09 21 sets		23.76
	Average	12.0	5.0	19.1	23.0	23.8

Notes  
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	11/20/2014 11:15
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 25 degC, 13 %rH
Test End Date and Time:	12/2/2014 12:08
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (application)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard ext tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	23.67	10.14	20.38	23.60	26.80
			( 1 set )	5 sets	29 sets	
	1:2	31.68	7.56	10.48		13.56
B&W mode	1:1	19.82	12.11	21.13	24.30	26.80
			( 1 set )	3 sets	29 sets	
	1:2	31.03	7.72	10.66		13.56
B&W mode	2:2	33.29	7.20	10.48		13.56
			( 1 set )	3 sets	3 sets	

Notes  
Reports located: <http://www.hp.com/go/printerclaims>

**ISO/IEC 24735 Copy Productivity Report**

Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	11/20/2014 11:15
Tester	KN
Machine name/model	ProXpress C2670FW
Colour or B&W	Colour
FW Version	V4.00.01.02 JUN-01-2014
Configuration (options)	Not Specified
Temperature and Humidity	76 degF / 25 degC, 13 %rH
Test End Date and Time:	12/2/2014 12:08
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (application)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard ext tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	23.50	10.19	19.62	22.91	25.82
			( 1 set )	5 sets	29 sets	
	1:2	34.14	7.02	10.14	<del>22.91</del>	13.04
B&W mode	1:1	19.70	12.17	20.51	23.45	25.83
			( 1 set )	3 sets	29 sets	
	1:2	31.82	7.52	10.48	<del>22.91</del>	13.06
B&W mode	2:2	34.04	7.04	10.16	<del>22.91</del>	13.06
			( 1 set )	3 sets	3 sets	

Notes  
 Reports located: <http://www.hp.com/go/printerclaims>