

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - LETTER

Xerox WorkCentre 6605DN

Printing device and settings		
Test Start Date and Time	6/6/2015 7:58	
Tester	BG	
Machine name/model	Xerox WorkCentre 6605DN	
Colour or B&W	Colour	
FW Version	201207201622	
Temperature and Humidity	79 degF / 26 degC, 36 %rH	
Voltage	110V	
Test End Date and Time	6/26/2015 14:29	

Item	Value	
Mode and Setting	Driver Version	v6.1.7601.17514
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Xerox Black and White Conversion
	Duplex B&W Settings	Xerox Black and White Conversion
	Setting N set count	Application
	Collating function	Activated (application)
Paper Path	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
	Duplexing Unit (Yes/No)	Yes
Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter			
	Office Category Test for Color Device	FSOT (seconds)	ESAT (ipm)
Color	Simplex	15.0	36.8
	Duplex	18.4	24.2
B&W	Simplex	14.0	36.8
	Duplex	17.7	24.2

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: LETTER						
	Office Category Test	FSOT (secs)	EFTP (ipm)			ESAT (ipm)
			1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	
Color Mode	Simplex - Adobe Reader	15.03	15.96 (1 set)	30.03 (6 sets)	31.66 (41 sets)	36.81
	Simplex - Word	15.00	15.99 (1 set)	30.42 (6 sets)		36.79
	Simplex - Excel	14.69	16.33 (1 set)	30.38 (6 sets)		36.80
	Simplex - Average	15.0	16.0	30.2	31.6	36.8
	Duplex - Adobe Reader	18.68	12.84 (1 set)	20.30 (5 sets)		24.28
	Duplex - Word	18.00	13.32 (1 set)	20.60 (5 sets)		24.28
	Duplex - Excel	18.34	13.06 (1 set)	20.66 (5 sets)		24.28
	Duplex - Average	18.4	13.0	20.5		24.2
B&W mode (optional for color device)	Simplex - Adobe Reader	14.02	17.11 (1 set)	30.69 (6 sets)	30.80 (41 sets)	36.80
	Simplex - Word	13.86	17.30 (1 set)	30.57 (6 sets)		36.79
	Simplex - Excel	13.86	17.33 (1 set)	30.69 (6 sets)		36.81
	Simplex - Average	14.0	17.2	30.6	30.8	36.8
	Duplex - Adobe Reader	18.50	12.96 (1 set)	20.68 (5 sets)		24.28
	Duplex - Word	17.30	13.86 (1 set)	21.04 (5 sets)		24.28
	Duplex - Excel	17.25	13.92 (1 set)	21.02 (5 sets)		24.28
	Duplex - Average	17.7	13.5	20.9		24.2

Notes
 1) All printing device and driver settings were default mode.
 2) For the B/W results, the print driver was set to "print in B/W".
 3) For more information see <http://www.hp.com/go/printerclaims>.
 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compaq Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCXHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/100
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 24734 Printing Productivity Report: Office Category

Full Detailed Test Report - A4

Xerox WorkCentre 6605DN

Printing device and settings		
Test Start Date and Time	6/6/2015 7:58	
Tester	BG	
Machine name/model	Xerox WorkCentre 6605DN	
Colour or B&W	Colour	
FW Version	201207201622	
Temperature and Humidity	79 degF / 26 degC, 36 %rH	
Voltage	110V	
Test End Date and Time	6/26/2015 14:29	

Item	Value	
Mode and Setting	Driver Version	v6.1.7601.17514
	Media/Quality Setting	Default / Default
	Simplex B&W Settings	Xerox Black and White Conversion
	Duplex B&W Settings	Xerox Black and White Conversion
	Setting N set count	Application
Paper Path	Collating function	Activated (application)
	Paper Sending Direction	Default
	Paper Size Setting	Default
	Paper Feeding	Tray 2
	Paper Exit	Standard Exit Tray
	Output Orientation	Default (face down)
Paper	Duplexing Unit (Yes/No)	Yes
	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4			
Office Category	Test for Color Device	FSOT (seconds)	ESAT (ipm)
Colour	Simplex	15.3	35.0
	Duplex	18.8	23.5
B&W	Simplex	14.6	35.0
	Duplex	18.2	23.5

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.

Detailed Report: A4

	Office Category Test	FSOT (secs)		EFTP (ipm)		ESAT (ipm)	
		1 set only (1 set)	1 set only (1 set)	1 set + 30sec (# of sets)	1 set + 4min (# of sets)	1 set + 30sec	1 set + 30sec
Colour Mode	Simplex - Adobe Reader	15.42	15.55 (1 set)	29.00 (6 sets)	27.72 (39 sets)		35.04
	Simplex - Word	14.91	16.09 (1 set)	29.18 (6 sets)			35.04
	Simplex - Excel	15.34	15.64 (1 set)	28.41 (6 sets)			35.03
	Simplex - Average	15.3	15.7	28.8	27.7		35.0
	Duplex - Adobe Reader	18.95	12.66 (1 set)	19.90 (5 sets)			23.50
	Duplex - Word	18.43	13.02 (1 set)	20.14 (5 sets)			23.50
	Duplex - Excel	18.99	12.62 (1 set)	20.12 (5 sets)			23.50
	Duplex - Average	18.8	12.7	20.0			23.5
B&W mode (optional for color device)	Simplex - Adobe Reader	14.65	16.37 (1 set)	29.36 (6 sets)	29.21 (39 sets)		35.04
	Simplex - Word	14.20	16.89 (1 set)	29.88 (6 sets)			35.04
	Simplex - Excel	14.80	16.21 (1 set)	29.48 (6 sets)			35.04
	Simplex - Average	14.6	16.4	29.5	29.2		35.0
	Duplex - Adobe Reader	18.86	12.70 (1 set)	20.04 (5 sets)			23.50
	Duplex - Word	17.58	13.64 (1 set)	20.38 (5 sets)			23.50
	Duplex - Excel	17.91	13.38 (1 set)	20.14 (5 sets)			23.50
	Duplex - Average	18.2	13.2	20.1			23.5

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.

Test System Parameters	
Item	Value
Computer	HP Compag Elite 8300 Small Form Factor
Processor	Intel Core i7 -3770, 3.4 GHz
System Chip Set	Intel C216 Chipset Family SMBus Host Controller
System Board	system devices, default system BIOS
System Memory	4 GB
Hard Drive Subsystem	Standard disk drive (Seagate)
Video Subsystem	AMD Radeon HD 6350
Optical Drive	HP DVD A DH16aCSHR ATA
I/O Subsystem	Builtin
USB Subsystem	USB 2.0/3.0
TCP/IP	TCP/IP 10/1000
Operating System	Windows 7 64 Bit
Printing Applications	Microsoft Office 2010
Microsoft Office	Office 2010
Adobe Reader	10
Test files and location	Office category files, hard drive

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - LETTER

Xerox WorkCentre 6605DN

Printing device and settings	
Test Start Date and Time	6/3/2015 11:58
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622
Configuration (options)	Default
Controller	02.00.00
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	78 degF / 26 degC, 25 %rH
Voltage	110V
Test End Date and Time	8/4/2015 8:15

Item	Value	
Mode and Setting	PDL and driver version	v6.1.7601.17514
	Print Quality mode	default
	B&W settings	default
Paper	Paper feed orientation	Short Edge
	Paper type setting	default
Paper Path	Paper feeding	Standard cassette
	Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: Letter		
		FPOT from Ready (seconds)
Color	Simplex	9.93
	Duplex	13.39
B&W	Simplex	9.01
	Duplex	12.64

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: LETTER						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Color Mode	FPOT from Ready - Simplex	9.43	9.99	10.37	9.93	48 Seconds
	FPOT from Ready - Duplex	13.06	13.46	13.64	13.39	48 Seconds
	FPOT from Sleep - Simplex			23.17		65 Minutes
	Recovery Time			12.8		
	FPOT from Off - Simplex			60.01		
	Warm-up Time			49.64		
B&W Mode	FPOT from Ready - Simplex	8.81	8.88	9.33	9.01	48 Seconds
	FPOT from Ready - Duplex	11.88	12.30	13.73	12.64	48 Seconds
	FPOT from Sleep - Simplex			22.75		65 Minutes
	Recovery Time			13.4		
	FPOT from Off - Simplex			52.22		
	Warm-up Time			42.89		

- Notes
- 1) All printing device and driver settings were default mode.
 - 2) For the B/W results, the print driver was set to "print in B/W".
 - 3) For more information see <http://www.hp.com/go/printerclaims>.
 - 4) Port monitor not configured to follow device if the IP address changes.
 - 5) Page counts were collected after completion of the tests.

Test System Parameters			
Item	Value		
Test System	Computer	HP Compaq Elite 8300 Small Form Factor	
	Processor	Intel Core i7 -3770, 3.4 GHz	
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller	
	System Board	system devices, default system BIOS	
	System Memory	4 GB	
	Hard Drive Subsystem	Standard disk drive (Seagate)	
	Video Subsystem	AMD Radeon HD 6350	
	Optical Drive	HP DVD A DH16aCSHR ATA	
	I/O Subsystem	Builtin	
	USB Subsystem	USB 2.0/3.0	
Printing Device Connection	TCP/IP	10/1000	
	Software		
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1	
	Printing Applications	Microsoft Office 2010 SP2	
	Print Driver	Adobe Reader 10.1.4	

ISO/IEC 17629 First Print Out Time Report: Office Category

Full Detailed Test Report - A4
Xerox WorkCentre 6605DN

Printing device and settings	
Test Start Date and Time	6/3/2015 11:58
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622

Configuration (options)	Default
Controller	02.00.00
Printing device page count	Not Specified
Printing supplies page count	Not Specified
Temperature and Humidity	78 degF / 26 degC, 25 %rH
Voltage	110V
Test End Date and Time	8/4/2015 8:15

Mode and Setting	Item	Value
	PDL and driver version	v6.1.7601.17514
	Print Quality mode	default
	B&W settings	default
	Paper feed orientation	Short Edge
Paper	Paper type setting	default
	Paper feeding	Standard cassette
	Paper exit	Standard exit tray
Paper Path	Output orientation	default (face up or face down)

ISO First Page Out Time Summary Report: Office Category

Summary Report: A4		
		FPOT from Ready (seconds)
Colour	Simplex	10.08
	Duplex	13.48
B&W	Simplex	9.25
	Duplex	12.99

Notes
1) All printing device and driver settings were default mode.
2) For the B/W results, the print driver was set to "print in B/W".
3) For more information see <http://www.hp.com/go/printerclaims>.
4) Port monitor not configured to follow device if the IP address changes.
5) Page counts were collected after completion of the tests.

ISO First Page Out Time Report: Office Category

Detailed Report: A4						
		Word (seconds)	Excel (seconds)	Adobe Reader (seconds)	Average (seconds)	Delay Time
Colour Mode	FPOT from Ready - Simplex	9.89	10.12	10.23	10.08	48 Seconds
	FPOT from Ready - Duplex	13.06	13.75	13.61	13.48	48 Seconds
	FPOT from Sleep - Simplex			23.67		65 Minutes
	Recovery Time			13.4		
	FPOT from Off - Simplex			61.36		
	Warm-up Time			51.13		
B&W Mode	FPOT from Ready - Simplex	8.84	9.84	9.06	9.25	48 Seconds
	FPOT from Ready - Duplex	12.13	13.01	13.80	12.99	48 Seconds
	FPOT from Sleep - Simplex			22.66		65 Minutes
	Recovery Time			13.6		
	FPOT from Off - Simplex			55.85		
	Warm-up Time			46.79		

Notes
1) All printing device and driver settings were default mode.
2) For the B/W results, the print driver was set to "print in B/W".
3) For more information see <http://www.hp.com/go/printerclaims>.
4) Port monitor not configured to follow device if the IP address changes.
5) Page counts were collected after completion of the tests.

Test System Parameters

Test System	Item	Value
	Computer	HP Compaq Elite 8300 Small Form Factor
	Processor	Intel Core i7 -3770, 3.4 GHz
	System Chip Set	Intel C216 Chipset Family SMBus Host Controller
	System Board	system devices, default system BIOS
	System Memory	4 GB
	Hard Drive Subsystem	Standard disk drive (Seagate)
	Video Subsystem	AMD Radeon HD 6350
	Optical Drive	HP DVD A DH16aC5HR ATA
	I/O Subsystem	Builtin
	USB Subsystem	USB 2.0/3.0
Printing Device Connection	TCP/IP	10/1000
Software	Operating System	Windows 7 Business/Ultimate, 64 bit, Build 7601, SP 1
	Printing Applications	Microsoft Office 2010 SP2
		Adobe Reader 10.1.4
	Print Driver	v6.1.7601.17514

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - LETTER

Xerox WorkCentre 6605DN

Machine Setup Information	
Test Start Date and Time	6/8/2015 4:11
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622
Configuration (options)	Not Specified
Temperature and Humidity	79 degF / 26 degC, 41 %rH
Test End Date and Time:	6/17/2015 7:33

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: Letter		
	sFCOT	sESAT (ipm)
Color	15.4	36.8
B&W	11.7	36.8

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

Detailed Report: LETTER						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Color	A	15.30	3.92	25.84 21 sets	31.42 99 sets	36.81
	B	14.28	4.19	26.84 21 sets		36.81
	C	16.22	3.69	25.90 21 sets		36.81
	D	15.43	3.88	25.93 21 sets		36.81
	Average	15.4	3.9	26.1	31.4	36.8
B&W	A	12.21	4.91	28.02 21 sets	31.26 99 sets	36.81
	B	12.54	4.78	27.66 21 sets		36.80
	C	10.93	5.48	28.91 21 sets		36.81
	D	10.95	5.47	27.78 21 sets		36.81
	Average	11.7	5.1	28.0	31.2	36.8

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

ISO/IEC 29183 Copy Productivity Report

Full Detailed Test Report - A4

Xerox WorkCentre 6605DN

Machine Setup Information	
Test Start Date and Time	6/8/2015 4:11
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622
Configuration (options)	Not Specified
Temperature and Humidity	79 degF / 26 degC, 41 %rH
Test End Date and Time:	6/17/2015 7:33

	Pre-set Item	Pre-set Value
Mode	Output Resolution	Default
	Output Quality	Default
	Copying Mode	Colour for Colour and B&W for B&W
	Auto Density Adjustment	Default
	Collating function	Set in Control Panel
Paper	Paper Sending Direction	Default
	Paper Type Setting	Default
Paper Path	Paper Feeding	Tray 2
	Paper Exit	Default
	Face Up Exit	Default (face down)
Temporary Stop	Fixing Capability	Default
	Image Quality Stability	Default
	Capacity of Paper	Default
	Others	None

Paper	Paper Manufacturer	HP / Xerox
	Paper Weight	20lb / 75 g/m2
	Paper Size	Letter / A4
	Paper type/name	HP Multipurpose Ultra White / HP Office

Summary Report: A4		
	sFCOT	sESAT (ipm)
Colour	15.2	35.0
B&W	12.9	35.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

Detailed Report: A4						
	Target	sFCOT (secs)	sEFTP (ipm)			sESAT (ipm)
			1copy	1copy+30sec	1copy+4minutes	
Colour	A	13.86	4.32	25.66 20 sets	30.01 99 sets	35.05
	B	15.44	3.88	25.19 20 sets		35.04
	C	15.31	3.91	25.24 20 sets		35.04
	D	16.04	3.73	25.88 20 sets		35.04
	Average	15.2	3.9	25.4	30.0	35.0
B&W	A	12.66	4.74	26.88 20 sets	29.91 99 sets	35.04
	B	12.96	4.62	27.56 20 sets		35.05
	C	12.72	4.71	26.57 20 sets		35.06
	D	13.03	4.59	26.27 20 sets		35.05
	Average	12.9	4.6	26.8	29.9	35.0

Notes
 First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration and document.
 NOTE: Copy count is limited to 99 by the Control Panel, which prevents the 4 minute test from achieving 4 minutes.

ISO/IEC 24735 Copy Productivity Report

Full Detailed Test Report - LETTER

Machine Setup Information	
Test Start Date and Time	12/5/2012 18:56
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 29 %rH
Test End Date and Time	12/5/2012 22:07

Pre-set Item	Pre-set Value
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: LETTER						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Color Mode	1:1	28.02	8.56	24.89	29.60	35.50
			(1 set)	7 sets	35 sets	
	1:2	30.96	7.74	17.90		24.28
			(1 set)	6 sets		
	2:2	40.09	5.98	14.34		22.04
			(1 set)	5 sets		
B&W mode	1:1	19.05	12.60	28.58	30.54	35.91
				7 sets	36 sets	
	1:2	23.97	10.00	19.18		24.28
				6 sets		
	2:2	31.76	7.54	15.94		22.10
				5 sets		

Notes
Reports located: <http://www.hp.com/go/printerclaims>

ISO/IEC 24735 Copy Productivity Report
Full Detailed Test Report - A4

Machine Setup Information	
Test Start Date and Time	12/5/2012 18:56
Tester	BG
Machine name/model	Xerox WorkCentre 6605DN
Colour or B&W	Colour
FW Version	201207201622
Configuration (options)	Not Specified
Temperature and Humidity	75 degF / 24 degC, 29 %rH
Test End Date and Time	12/5/2012 22:07
Pre-set Item	
Pre-set Value	
Output Resolution	Default
Output Quality	Default
Copying Mode	Default
Auto Density Adjustment	Default
Collating function	Activated (if not activated in default mode)
Paper Sending Direction	Default
Paper Type Setting	Default
Paper Feeding	Standard cassette
Paper Exit	Standard exit tray
Face Up Exit	Default
Fixing Capability	Default
Image Quality Stability	Default
Capacity of Paper	Default
Others	Default
Paper Manufacturer	HP / Xerox
Paper Weight	20lb / 75 g/m2
Paper Size	Letter / A4

ISO/IEC 24735 Copy Productivity Report						
Detailed Report: A4						
	Copying Mode	FSOT (secs)		EFTP (ipm)		ESAT (ipm)
		1 set only	1 set only	1 set + 30sec	1 set + 4min	1 set + 30sec
Colour Mode	1:1	27.14	8.83 (1 set)	22.97 6 sets	28.14 33 sets	33.71
	1:2	31.04	7.72 (1 set)	17.52 6 sets		23.50
	2:2	40.64	5.90 (1 set)	13.44 5 sets		23.50
B&W mode	1:1	18.99	12.63	27.50 7 sets	29.19 35 sets	34.23
	1:2	24.85	9.66	19.18 6 sets		23.50
	2:2	32.32	7.42	15.58 5 sets		21.50
Notes						
Reports located: http://www.hp.com/go/printerclaims						