HP recommends Windows[®] 7.



Versatility redefined, still compact.

Big Possibilities. Compact Form Factor.

With its innovative design, the HP Z620 Workstation gives you a near silent computing solution in a form factor that's a perfect fit for space-constrained environments. And for easy servicing and upgrades, it features a completely tool-less chassis with integrated handles and a tool-free power supply.

The Performance You Demand.

Get massive system performance with a small footprint. The HP Z620 features the next evolution in processor technology and system architecture, setting the standard for versatility with support for a single Intel[®] Xeon[®] processor E5-1600 or dual Intel[®] Xeon[®] processor E5-2600 series.^{1,2,3,4} Now with up to 16 cores, the HP Z620 powerhouse supports a full range of processors, to help you get more done every minute.

Bring Your Ideas To Life Faster.

The HP Z620 is designed to support next generation PCI express Gen3 graphics technology that doubles the bandwidth in and out of the card. The HP Z620 offers a huge variety of professional graphics from NVIDIA and AMD from Pro 2D to Extreme 3D. And with 800W 90% efficient power supply and support for up to 8 displays, the HP Z620 gives you the freedom of doing and seeing more.

Modify Your Machine.

Customize the HP Z620 Workstation the way you want to with a variety of expansion options, including USB 3.0 for blazing fast speeds and up to 12 memory slots capable of supporting 96GB of the latest generation of DDR3 memory. With 3 internal drive bays and 2 external bays, choose from a variety of storage types including SATA 7.2K/10K, SAS 10K/15K and SSD.

HP Z620 Workstation

HP recommends Windows[®] 7.

www.hp.com/zworkstations

Form Factor	Rackable minitower							
Available Operating Systems	Genuine Windows® 7 Professional 32:Bit Genuine Windows® 7 Professional 64-bit HP Linux Installer Kit* SUSE Linux Enterprise Desktop 11 * Red Hat Enterprise Linux Desktop/Workstation (1 year paper license; no preinstalled OS)*							
Available Processors ^{1,2,3,4}	Processor	GHz	Cache	Memory	Cores	Hyper- Threading	Featuring Intel® vPro™ Technology	Intel® Turbo Boost Technology⁵
	Intel® Xeon® Processor E5-2690	2.9	20 MB	, 1600 MHz	8	Y	Y	4, 9
	Intel [®] Xeon [®] Processor E5-2680	2.7	20 MB	1600 MHz	8	Ý	Ý	4, 8
	Intel [®] Xeon [®] Processor E5-2670	2.6	20 MB	1600 MHz	8	Y	Y	4, 7
	Intel [®] Xeon [®] Processor E5-2667	2.9	15 MB	1600 MHz	6	Y	Y	3, 6
	Intel [®] Xeon [®] Processor E5-2665	2.4	20 MB	1600 MHz	8	Y	Y	4, 7
	Intel [®] Xeon [®] Processor E5-2660	2.2	20 MB	1600 MHz	8	Y	Y	5, 8
	Intel [®] Xeon [®] Processor E5-2650	2	20 MB	1600 MHz	8	Y	Y	4, 8
	Intel [®] Xeon [®] Processor E5-2643	3.3	10 MB	1600 MHz	4	Y	Y	1, 2
	Intel [®] Xeon [®] Processor E5-2640	2.5	15 MB	1333 MHz	6	Y	Y	3, 5
	Intel [®] Xeon [®] Processor E5-2630	2.3	15 MB	1333 MHz	6	Y	Y	3, 5
	Intel [®] Xeon [®] Processor E5-2620	2	15 MB	1333 MHz	6	Y	Y	3, 5
	Intel [®] Xeon [®] Processor E5-2609	2.4	10 MB	1066 MHz	4	Ν	Y	N/A
	Intel [®] Xeon [®] Processor E5-2603	1.8	10 MB	1066 MHz	4	Ν	Y	N/A
	Intel [®] Xeon [®] Processor E5-1660	3.3	15 MB	1600 MHz	6	Y	Y	3, 6
	Intel [®] Xeon [®] Processor E5-1650	3.2	12 MB	1600 MHz	6	Y	Y	3, 6
	Intel [®] Xeon [®] Processor E5-1620	3.6	10 MB	1600 MHz	4	Y	Y	2, 3
	Intel [®] Xeon [®] Processor E5-1607	3	10 MB	1066 MHz	4	Ν	Y	N/A
	Intel® Xeon® Processor E5-1603	2.8	10 MB	1066 MHz	4	N	Y	N/A
Chipset	Intel® C602 Chipset							
Memory ⁶	Up to 12 DIMM slots with 2 CPUs, up to 96 GB, 8-channel ECC DDR3 1600 MHz; 4 channels per CPU							
Drive Controllers	Integrated SATA 6 Gb/s controller, RAID 0, 1, 5, 10 capable; Optional SAS controller: LSI 9212-4i 4-port SAS 6 Gb/s RAID 0, 1, 10 capable							
Storage ^{7,8}	Up to (4) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2, 3 TB, 11 TB max; Up to (4) 2.5-inch 10K rpm SAS drives: 300, 600 GB, 2.4 TB max; Up to (4) 3.5-inch 15K rpm SAS drives: 300, 450, 600 GB, 2.4 TB max; Up to (4) 2.5-inch SATA solid state drives: 128, 160, 256, 300 GB, 1.2 TB max; Note: Fourth drive occupies one external 5.25-inch bay							
Optical Storage ^{9,10}	DVD-ROM, DVD+/-RW, Slot-load DVD+/-RW, Blu-ray Writer, 22-in-1 Media Card Reader							
Drive Bays	2 external 5.25-inch bays, 3 internal 3.5-inch bays, Note: Fourth HDD occupies one external bay							
Expansion Slots	2 PCI Express Gen3 x16; 1 PCI Express Gen3 x8, 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 PCI Express Gen2 x4 mechanical/x1 electrical; 1 Legacy PCI							
Available Graphics	Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310,** NVIDIA Quadro NVS 450, AMD FirePro™ 2270 Entry 3D: NVIDIA Quadro 410,** NVIDIA Quadro 600, AMD FirePro™ V3900, AMD FirePro™ V4900 Mid-range 3D: NVIDIA Quadro 2000, AMD FirePro™ V5900 High-end 3D: NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro 5000, NVIDIA Quadro 6000, NVIDIA Tesla C2075							
Audio	Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speakers							
	Dual integrated Intel LAN; Infineon TPM 1.2 Controller; Optional Broadcom NIC; Optional Intel NIC							
Network	Dual integrated Intel LAN; Infineon TPM	1.2 Controller	Optional Bro	oadcom NIC; Op	tional Intel N			
	Dual integrated Intel LAN; Infineon TPM Front: 2 USB 3.0, 1 USB 2.0, 1 IE Rear: 2 USB 3.0, 4 USB 2.0, 1 a Internal: 5 USB 2.0	EE 1394a star	Idard, 1 micro	ophone in, 1 hea	dphone out,	HP 22-in-1 Med		
Network	Front: 2 USB 3.0, 1 USB 2.0, 1 IE Rear: 2 USB 3.0, 4 USB 2.0, 1 a	EE 1394a star udio in, 1 aud keyboard, US	idard, 1 micro io out, 1 micro B Smart Card	ophone in, 1 hea ophone in, 2 PS/ Keyboard, PS/2	dphone out, '2, 2 RJ-45 to	HP 22-in-1 Med integrated Gig	abit LAN, 1 serial via op	tional adapter
Network Ports	Front: 2 USB 3.0, 1 USB 2.0, 1 IE Rear: 2 USB 3.0, 4 USB 2.0, 1 a Internal: 5 USB 2.0 PS/2 standard keyboard, USB standard	EE 1394a star udio in, 1 aud keyboard, US Pilot, USB Lase	idard, 1 micro io out, 1 micro B Smart Card	ophone in, 1 hea ophone in, 2 PS/ Keyboard, PS/2	dphone out, '2, 2 RJ-45 to	HP 22-in-1 Med integrated Gig	abit LAN, 1 serial via op	tional adapter
Network Ports Input Devices	Front: 2 USB 3.0, 1 USB 2.0, 1 IE Rear: 2 USB 3.0, 4 USB 2.0, 1 a Internal: 5 USB 2.0 PS/2 standard keyboard, USB standard mouse, USB SpaceExplorer, USB Space	EE 1394a star udio in, 1 aud keyboard, USI Pilot, USB Lase 16.48 cm)	idard, 1 micro io out, 1 micro B Smart Card	ophone in, 1 hea ophone in, 2 PS/ Keyboard, PS/2	dphone out, '2, 2 RJ-45 to	HP 22-in-1 Med integrated Gig	abit LAN, 1 serial via op	tional adapter
Network Ports Input Devices Dimensions (H x W x D)	Front: 2 USB 3.0, 1 USB 2.0, 1 IE Rear: 2 USB 3.0, 4 USB 2.0, 1 a Internal: 5 USB 2.0 PS/2 standard keyboard, USB standard mouse, USB SpaceExplorer, USB SpaceE 17.5 x 6.75 x 18.3 in (44.45 x 17.15 x 4)	EE 1394a star udio in, 1 aud keyboard, US rilot, USB Lase I6.48 cm) supply isplay (24-inch ponitor, HP ZR2	dard, 1 micro io out, 1 micro 3 Smart Card r Scroll Mouse diagonal wic 4w 24-inch S	pophone in, 1 hea ophone in, 2 PS/ Keyboard, PS/2 escreen), HP ZR3 IPS LCD Monitor,	dphone out, (2, 2 RJ-45 tc optical scrol 30w 30-inch HP LP2475v	HP 22-in-1 Med o integrated Gig I mouse, USB 2-1 S-IPS LCD Monit v 24-inch Wides	abit LAN, 1 serial via op outton optical scroll mous or, HP ZR2740w 27-inch l	itional adapter e, USB 3-button optical .ED Backlit IPS Monitor,

Linux available 2nd calendar quarter 2012 (CQ2'12)

Available June/July 2012

Dual-, Quad-, Six- and Eight-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating 2

system software for full benefits; Not all customers or software applications will necessarily benefit from use of these technologies. 64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel® 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See http://www.intel.com/info/em64t for more infor info/em64t for more information.

5

6 7

8

9

Carbon computing on intel[®] architecture requires a computer system with a processor, chipser, biOS, operating system, aevice drivers and applications enabled for intel[®] of architecture. Processors with nor operate (including 32-bit operation) without an Intel[®] of architecture-enabled BIOS. Performance will vary depending on your hardware and software and software configurations. See http://www.intel.com/info/em64b for more information. Intel's numbering is not a measurement of higher performance. Z620 systems configured with E5-1600 series processors may not add a 2nd processor. To support two processors, E5-2600 series processor must be chosen. The specifications shown in this column represent the following: (all core maximum turbo steps, one core maximum turbo steps). Turbo boost stepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. Intel[®] Turbo Boost technology requires a PC with a processor with Intel[®] Turbo Boost capability. Intel[®] Turbo Boost performance varies depending on hardware, software, and overall system configuration. Please visit http://www.intel.com/technology/turboboost for more information. Each processor supports up to 4 channels of DDR3 memory. To realize full performance at least 1 DIMM must be inserted into each channel. SATA hardware RAID is not supported on Linux systems. The Linux kernel, with builtin software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit http://hcosv.pp.com/bc/docs/support/Suppor 10 11 Lookup Tool at http://www.hp.com/go/looku vary depending on your geographic location.



© 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.